



Mobil Delvac™ Super 1400 15W-40

Mobil Commercial Vehicle Lube , Australia

High Performance Diesel Engine Oil

Product Description

Mobil Delvac Super 1400 15W-40 is a high performance diesel engine oil that provides protection of diesel engines operating on and off-highway applications. Mobil Delvac Super 1400 15W-40 is recommended by ExxonMobil for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

Features and Benefits

The technology in Mobil Delvac Super 1400 15W-40 delivers excellent performance in both modern diesel engines as well as older models. The key benefits include:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
TBN reserve	Deposit control
Stay-in-grade shear stability	Reduced oil consumption and wear protection
Excellent detergency/dispersancy	Clean engines and long engine life
Component compatibility	Long gasket and seal life

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying, and agriculture

Specifications and Approvals

This product has the following approvals:
MB 228.3

This product is recommended for use in applications requiring:
ACEA E3

This product is recommended for use in applications requiring:

API CF

API CF-4

API CG-4

Mack EO-M

VOLVO VDS-2

This product meets or exceeds the requirements of:

API CH-4

API SJ

Cummins CES 20076

Properties and Specifications

Grade	SAE 15W-40
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	116
Pour Point, °C, ASTM D97	-33
Total Base Number, mgKOH/g, ASTM D2896	8
Viscosity Index, ASTM D2270	137
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	15.2
Flash Point, Cleveland Open Cup, °C, ASTM D92	233
Density @ 15 C, kg/l, ASTM D4052	0.869
Ash, Sulfated, mass%, ASTM D874	1.1

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2023

Mobil Oil Australia Pty Ltd

A.B.N. 88 004 052 984

12 Riverside Quay

Southbank Vic 3006

+61 3 8633 8444

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to

change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved