



Mobil™ Compressor Oil 150 IR

Mobil Industrial , Australia

Gas Compressor Cylinder Lubricant

Product Description

Mobil Compressor Oil 150 IR is a premium quality compounded lubricant specially developed for cylinder lubrication of gas compressors. Compressor Oil 150 IR is recommended by ExxonMobil for use in reciprocating compressors with separate cylinder lubrication systems operating on natural gas or other hydrocarbon gases. Mobil Compressor Oil 150 IR is formulated from high quality mineral base oil and selected additives to give excellent thermal and oxidative stability helping to minimize harmful carbon deposit formation on exhaust valves, pistons, rods and packings. This lubricant also has excellent film strength that resists wash-off by wet gases or hydrocarbons in the gas which may condense during compression.

Features and Benefits

The use of the Mobil Compressor Oil 150 IR can result in cleaner compressors and lower deposits compared to conventional mineral oils, resulting in longer running periods between maintenance intervals. This product's excellent oxidation and thermal stability safely allow extended life capability while controlling sludge and deposit formation. It possesses outstanding anti-wear and corrosion protection, which enhances equipment life and performance.

| Features | Advantages and Potential Benefits |
|-------------------------------------------|----------------------------------------------------------------------------------------------------|
| Low Carbon Deposit Formation | Helps improve valve response and performance |
| | Helps reduce deposits in discharge lines |
| | Helps extend equipment life and contributes to reduced maintenance costs |
| Excellent Oxidation and Thermal Stability | Long oil life |
| | Helps improve filter life and lower maintenance costs |
| | Helps reduce deposit formation |
| Excellent Wear Protection | Provides effective lubricating film helping to reduce wear of rings, cylinders, bearings and gears |
| Excellent Water Resistance | Resists wash off by wet gases, helping to maintain equipment lubrication and protection |
| Effective Rust and Corrosion Protection | Helps improve protection of valves and reduce wear of rings and cylinders |

Applications

Recommended for cylinder lubrication in reciprocating compressors with separate cylinder lubrication systems operating on natural gas or other hydrocarbon gases. Suitable for use over a wide range of operating temperatures typically found in an oil and gas production environment.

Typical Properties

| Mobil Compressor Oil 150 IR | |
|------------------------------------|--------|
| ISO VG | 150 |
| Density @ 15°C, Kg/l (ASTM D 4052) | 0.8959 |
| Foam Test (ASTM D 892, Seq I) | 0/0 |
| Viscosity cSt @100°C (ASTM D 445) | 16.4 |
| Zn-content (ASTM D 4951) | 0.03 |

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2019

Mobil Oil Australia Pty Ltd

A.B.N. 88 004 052 984

12 Riverside Quay

Southbank Vic 3006

+61 3 8633 8444

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon

Mobil



© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved