



Mobil™ Formula S2 10W-40
Mobil Passenger Vehicle Lube , Australia
Premium Semi-synthetic Engine Oil

Product Description

Mobil™ Formula S2 10W-40 is a premium semi-synthetic engine oil, formulated to provide engine protection beyond that of conventional engine oils

Features and Benefits

"Mobil™ Formula S2 10W-40 is formulated to provide engine protection beyond that of conventional engine oils.

Mobil™ Formula S2 10W-40 provides:

- Outstanding wear protection
- Excellent engine cleanliness
- High temperature protection

Applications

Mobil™ Formula S2 10W-40 is suitable for use in gasoline, LPG and light to medium diesel powered vehicles. It is ideally suited for normal to occasionally severe operating conditions, highway cruising and some high performance applications.

Specifications and Approvals

This product has the following approvals:
MB-Approval 229.1
VW 501 01
VW 505 00

This product is recommended by ExxonMobil for use in applications requiring:
API CF

This product meets or exceeds the requirements of:
API SL
API SJ
API SM
API SN

This product meets or exceeds the requirements of:
API SN PLUS
ACEA A3/B3

Properties and Specifications

Property	
Grade	SAE 10W-40
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	95
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	14.2
Flash Point, Cleveland Open Cup, °C, ASTM D92	234
Density @ 15.6 C, g/ml, ASTM D4052	0.867
Viscosity Index, ASTM D2270	155
Pour Point, °C, ASTM D97	-33

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2022
Mobil Oil Australia Pty Ltd
A.B.N. 88 004 052 984
12 Riverside Quay
Southbank Vic 3006
+61 3 8633 8444
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved