



MOBIL 1 RACING™ OILS

Mobil Passenger Vehicle Lube , Australia

Advanced Full Synthetic Motor Oil

Product Description

Mobil 1™ Racing oils are advanced full synthetic motor oils designed specifically for racing engines and are not recommended for street use. These high performance, fully synthetic formulas are specially balanced for friction reduction and optimum horsepower with outstanding wear protection.

Features and Benefits

Mobil 1 Racing oils are proprietary formulations of low viscosity synthetic base oils fortified with a precisely balanced component-blended additive system featuring high levels of anti-wear and friction reducing additives. This advanced protection is engineered to help deliver optimum horsepower with outstanding wear protection. Key features and potential benefits include:

- Boosted levels of anti-wear protection -- well beyond those of ordinary automotive oils -- to help protect engines even during grueling racing applications.
- Helps to maximize power output by reducing internal friction.
- Outstanding shear stability and a robust additive package to help reduce oil breakdown and help to extend engine life, even under some of the most extreme conditions.
- Compared to conventional racing oils and higher-viscosity synthetic motor oils, it provides faster flow to critical engine parts at low temperatures.
- Helps to deliver exceptional high-temperature protection, even at temperatures in excess of 400 degrees F (204 C).

Applications

Mobil 1 Racing oils are recommended by ExxonMobil for a wide range of race engine applications. Note: Mobil 1 Racing oils are not recommended for street use.

- Mobil 1 Racing oils are recommended by ExxonMobil for a wide range of race engine applications including highly loaded flat tappet designs such as NASCAR Cup engines.
- Mobil 1 Racing oils are designed for use by professional, amateur and weekend racers.
- Mobil 1 Racing oils are not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.

Properties and Specifications

Property	0W-30	0W-50
Grade	SAE 0W-30	SAE 0W-50
Ash, Sulfated, mass%, ASTM D874	1.3	1.3
Density @ 15.6 C, g/ml, ASTM D4052	0.85	0.85
Flash Point, °C, ASTM D92	217	221
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.3	3.8
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	11.5	17.2
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	63.5	100
Pour Point, °C, ASTM D97	-54	-54

Property	0W-30	0W-50
Viscosity Index, ASTM D2270	178	189

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2020

Mobil Oil Australia Pty Ltd

A.B.N. 88 004 052 984

12 Riverside Quay

Southbank Vic 3006

+61 3 8633 8444

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved