



Mobil 1™ ESP X4 0W-40

Mobil Passenger Vehicle Lube , Australia

Advanced Multigrade Synthetic Four-Stroke Motorcycle Engine Oil

Product Description

Mobil 1™ ESP X4 0W-40 is an advanced full synthetic engine oil specifically designed to provide outstanding wear protection, engine cleanliness, and strong durability to keep your engine running like new.

Mobil 1™ ESP X4 0W-40 combines durability and protection with a low friction engine oil that was designed in cooperation with key European Original Equipment Manufacturers (OEMs).

Mobil 1™ ESP X4 0W-40 has been expertly engineered to help prolong the life and maintain the efficiency of emission systems in new emerging diesel and gasoline powered European vehicles that require SAE 0W-40 viscosity grades.

Features and Benefits

Mobil 1™ ESP X4 0W-40 is made with a proprietary blend of leading edge components formulated to be fully compatible with the latest Diesel Particulate Filters (DPF) and Gasoline Catalytic Converters (CAT). Mobil 1™ ESP X4 0W-40 has been designed to help deliver outstanding performance and protection.

Key features and potential benefits include:

- Reduce particulate buildup in diesel particulate filters
- Reduce poisoning of gasoline catalytic converters
- Reduce deposits and sludge buildup to enable long and clean engine life
- Reduce oil aging, allowing extended drain interval protection

Applications

Mobil 1™ ESP X4 0W-40 is recommended for high-performance gasoline and diesel engines in the latest passenger cars, SUVs and light vans that require SAE 0W-40 viscosity grades.

- Mobil 1™ ESP X4 0W-40 helps to protect exhaust gas after-treatment systems designed to limit engine emissions.
- Mobil 1™ ESP X4 0W-40 is not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.

Always consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade and specifications

Specifications and Approvals

This product has the following approvals:
Porsche A40
PORSCHE C40

This product has the following approvals:

VW 511 00

MB 229.52

MB 229.51

This product is recommended for use in applications requiring:

API CF

ACEA C2-21 Application Suitable

This product meets or exceeds the requirements of:

API SP

Recommended by ExxonMobil for applications requiring ACEA C2

FIAT FIAT 9.55535-S2

Properties and Specifications

Property	
Grade	SAE 0W-40
Total Base Number, mgKOH/g, ASTM D2896	9.1
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.8
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	13.9
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	72
Viscosity Index, ASTM D2270	201
Mini-Rotary Viscometer, Apparent Viscosity, -40 C, mPa.s, ASTM D4684	21100
Density @ 15 C, g/ml, ASTM D4052	0.846
Pour Point, °C, ASTM D97	-54
Flash Point, Cleveland Open Cup, °C, ASTM D92	230

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2024

Mobil Oil Australia Pty Ltd

A.B.N. 88 004 052 984

12 Riverside Quay

Southbank Vic 3006


+61 3 8633 8444

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved