



## Mobil™ Advanced Coolant Ready Mixed

Mobil Passenger Vehicle Lube , Australia

Ready to use Pre-diluted Coolant/Antifreeze

### Product Description

Mobil™ Advanced Coolant Ready Mixed is a ready to use, hybrid coolant technology, ethylene glycol type radiator coolant offering year-round protection against freezing, boiling and corrosion. It provides -18°C freezing point and 104°C boiling point in petrol engines. Coloured Green.

Product is recommended for passenger car and light commercial petrol and diesel engines, requiring a type A coolant.

Ready to use product. Do NOT dilute further.

### Features and Benefits

Recommended service life:

Application*	Maximum service intervals are the lesser of
Passenger Car and Light Commercial Vehicle	5 years or 250,000 km

For heavy duty diesel engines\* use Mobil Advanced Anti-Freeze Concentrate diluted with demineralised water at 50% or a suitable Mobil Delvac Modern Coolant.

\*Refer to your vehicle service manual for coolant requirement.

### Applications

Product is recommended by ExxonMobil as suitable for use in applications requiring AS 2108:2004 Type A.

### Properties and Specifications

Property	
pH, ASTM D1287	7.6-8.5
Reserve Alkalinity, ml, ASTM D1121	2.0 min
Specific Gravity 15.6 C, ASTM D1122	1.04-1.05
Freeze Point, C, ASTM D1177	-18
Color, Visual	Green

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2021

Mobil Oil Australia Pty Ltd

A.B.N. 88 004 052 984

12 Riverside Quay

Southbank Vic 3006

+61 3 8633 8444

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved