



Mobil Super™ ALL-IN-ONE PROTECTION C5 0W-20

Mobil Passenger Vehicle Lube , Australia

Fully Synthetic Engine Oil

Product Description

Mobil Super™ All-In-One Protection C5 0W-20 is brought to you by the makers of Mobil 1. This full synthetic engine oil is specifically designed to provide outstanding engine cleanliness, wear protection, advanced fuel economy and maintain the efficiency of the car exhaust Emission Reduction Systems in both diesel and gasoline powered automobiles.

Features and Benefits

- Heat Activated Anti-Wear™ molecules provides high temperature wear protection while keeping engine clean
- Help maintain the efficiency of the exhaust Emission Reduction Systems
- Improve fuel economy

Applications

Mobil Super™ All-In-One Protection C5 0W-20 is recommended for new emerging diesel and gasoline powered vehicles with Diesel Particulate Filters (DPF) & Catalytic Convertors.

Mobil Super™ All-In-One Protection C5 0W-20 is suitable for hybrid engines that require API SP, ACEA C5 specifications.

Specifications and Approvals

This product meets or exceeds the requirements of:

API SP

API SN PLUS

API SN

ACEA C5

Properties and Specifications

Property	
Grade	SAE 0W-20
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	2.6
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	8.4
Density @ 15.6 C, g/ml, ASTM D4052	0.84
Viscosity Index, ASTM D2270	174

Property	
Ash, Sulfated, mass%, ASTM D874	0.8
Flash Point, Cleveland Open Cup, °C, ASTM D92	226
Pour Point, °C, ASTM D97	-45
Total Base Number, mgKOH/g, ASTM D2896	7.9
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	43

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2024

Mobil Oil Australia Pty Ltd

A.B.N. 88 004 052 984

12 Riverside Quay

Southbank Vic 3006


+61 3 8633 8444

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved