



## Mobil Delvac Legend™ 15W-40 Heavy Duty

Mobil Commercial Vehicle Lube , Azerbaijan

High Performance Diesel Engine Oil.

### Product Description

Mobil Delvac Legend 15W-40 Heavy Duty is a Multigrade synthetic Blend diesel engine oil that provides protection for diesel engines operating under severe service conditions for both on- and off-highway applications. Mobil Delvac Legend 15W-40 Heavy Duty is recommended by ExxonMobil for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying and agricultural industries

### Features and Benefits

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Helps to control sludge build-up and deposits
TBN reserve	Helps to control deposits
Stay-in-grade shear stability	Helps to reduce oil consumption and to provide wear protection
Excellent detergency/ dispersancy	Helps to protect and to maintain engines clean
Component compatibility	Long gasket and seal life

### Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment of European, Japanese and American manufacturers in line with owner manual recommendations
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying and agriculture

### Specifications and Approvals

This product has the following approvals:
MB-Approval 228.3

This product is recommended for use in applications requiring:
ACEA E3
API CF
API CF-4

**This product is recommended for use in applications requiring:**

API CG-4

Mack EO-M

VOLVO VDS-2

**This product meets or exceeds the requirements of:**

API CH-4

API SJ

**Properties and Specifications**

Property	
Grade	SAE 15W-40
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	116
Pour Point, °C, ASTM D97	-33
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	15.2
Ash, Sulfated, mass%, ASTM D874	1.1
Flash Point, Cleveland Open Cup, °C, ASTM D92	233
Viscosity Index, ASTM D2270	137
Total Base Number, mgKOH/g, ASTM D2896	8
Density @ 15 C, kg/l, ASTM D4052	0.869

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2023

**ExxonMobil**

Exxon Mobil  

© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved