



Mobil™ 10W-40

Mobil Passenger Vehicle Lube , Azerbaijan

Premium Quality Multigrade Passenger Vehicle Engine Oil

Product Description

Mobil™ 10W-40 is a premium quality motor oil for many types of gasoline and diesel vehicles.

Features and Benefits

Mobil 10W-40 is formulated with a proprietary mixture of premium and super premium quality base oils with an additive technology delivering engine protection under a variety of driving conditions. Mobil 10W-40 reduces engine wear with excellent high and low temperature performance.

Applications

Mobil 10W-40 can be used in a variety of passenger vehicles , light trucks and vans, and for anyone seeking a dependable super premium quality product.

Specifications and Approvals

This product is recommended for use in applications requiring:

MB 229.1

This product meets or exceeds the requirements of:

ACEA A3/B3-16

API SJ

API SL

API SM

API SN

API SN PLUS

Properties and Specifications

Property	
Grade	SAE 10W-40
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	13.3
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	89.3
Density @ 15.6 C, g/ml, ASTM D4052	0.86

Property	
Pour Point, °C, ASTM D97	-39
Flash Point, Cleveland Open Cup, °C, ASTM D92	232
Ash, Sulfated, mass%, ASTM D874	1.0
Hi-Temp Hi-Shear Viscosity @ 150 C 1×10^6 sec ⁻¹ , mPa.s, ASTM D4683	3.6
Phosphorus, mass%, ASTM D4951	0.08


Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2023

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved