



Mobil Super™ 2000 XE C2 5W-30

Mobil Passenger Vehicle Lube , Azerbaijan

Premium Passenger Vehicle Engine Oil

Product Description

Mobil Super™ 2000 XE C2 5W-30 provides everyday protection with maximised wear protection to ensure long engine life for many types and ages of gasoline and diesel vehicles equipped with particulate filters or catalytic converters.

Features and Benefits

Mobil Super™ 2000 are premium engine oils and engineered to provide an excellent level of protection.

Mobil Super 2000 XE C2 5W-30 is designed to help:

- Fuel efficiency - resulting from low oil viscosity under high shear operating conditions (HTHS @150°C ≥ 2,9 mPa.s)
- Sludge prevention
- Engine cleanliness and high temperature protection
- Cold start-up performance

Applications

ExxonMobil recommends Mobil Super 2000 XE C2 5W-30 for :

- Vehicles requiring ACEA C2 engine oils
- Gasoline and Diesel engines with exhaust gas after-treatment systems such as catalytic converters and/or Diesel Particulate Filters (DPF)
- Passenger cars, SUV's, light trucks and vans
- Normal to occasionally severe operating conditions

Specifications and Approvals

This product is recommended for use in applications requiring:

FIAT 9.55535-S1

This product meets or exceeds the requirements of:

API SN

API SN PLUS

ACEA C2

Properties and Specifications

Property	
Grade	SAE 5W-30
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	9.9
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	56.6
Pour Point, °C, ASTM D97	-39
Flash Point, Cleveland Open Cup, °C, ASTM D92	207
Phosphorus, mass%, ASTM D4951	0.08
Ash, Sulfated, mass%, ASTM D874	0.7
Density @ 15.6 C, g/ml, ASTM D4052	0.854


Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2024

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved