



## Mobil Super 1000 X1 10W-40, 15W-40 and 20W-50

Mobil Passenger Vehicle Lube , Bosnia

### Product Description

The Mobil Super 1000 range of lubricants are premium mineral engine oils, designed to provide a high level of protection and performance.

### Features and Benefits

Mobil Super 1000 products are industry tested so you can trust you will get the performance you want from your vehicle.

Mobil Super 1000 X1 provides:

- Good wear protection
- Good engine cleanliness
- Good high temperature protection

### Applications

Mobil Super 1000 products have been formulated for use in nearly all vehicles. Mobil Super 1000 is suitable for:

- Nearly all engine technologies
- Gasoline and Diesel
- Passenger cars, SUV's, light trucks and vans
- Highway cruising
- Normal Operating Conditions

Mobil Super 1000 X1 20W-50 is also suitable for use in LPG vehicles.

ExxonMobil particularly recommend Mobil Super 1000 for daily driving under normal conditions. Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

Mobil Super 1000 X1 meets or exceeds the requirements of:	10W-40	15W-40	20W-50
API SL/SJ	X	X	X
ACEA A3/B3	X	X	X
Mobil Super 1000 X1 has the following builder approvals:	10W-40	15W-40	20W-50
VW 505 00	X	X	X
MB-Approval 229.1	X	X	X
Mobil Super 1000 X1 is recommended by ExxonMobil for use in applications requiring:	10W-40	15W-40	20W-50
API CF	X	X	X

### Typical Properties

Mobil Super 1000 X1 10W-40	10W-40	15W-40	20W-50
Viscosity, ASTM D 445			
cSt @ 40° C	97	107	162
cSt @ 100° C	14.4	14.4	18.7

Mobil Super 1000 X1 10W-40	10W-40	15W-40	20W-50
Sulfated Ash, wt%, ASTM D 874	0.91	0.91	0.93
Phosphorous	0.144	0.147	0.144
Flash Point, °C, ASTM D 92	230	230	233
Density @15° C kg/l, ASTM D 4052	0.87	0.89	0.89
Pour Point, °C, ASTM D 97	-30	-30	-30

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Mobil Super Motor Oil are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

05-2020

.

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTD

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved