



Mobil Monogrado Series

Mobil Passenger Vehicle Lube , Barbados

Conventional Monograde Engine Oil

Product Description

Mobil™ Monogrado 40 is a heavy duty engine oil primarily intended for use in gasoline automotive engines of passenger cars. It's formulated from high quality mineral base oils and an advanced additive system required for combustion engines where an API SL engine oil is recommended. It contains an effective balance of detergents and dispersants to minimize the formation of sludge and deposits, retain alkalinity (TBN) and reduce wear.

Features and Benefits

- Help promote engine cleanliness.
- Good protection against wear and corrosion.
- Extended intervals between oil drain.
- Low oil consumption."

Applications

Mobil Monogrado 40 is recommended for the lubrication of gasoline engines for passenger cars. It can also be used in gear and hydraulic applications if the builder approves the use of monogrades engine oils for these applications.

Specifications and Approvals

| This product is recommended by ExxonMobil for use in applications requiring: | MOBIL MONOGRADO 40 | MOBIL MONOGRADO 50 |
|--|--------------------|--------------------|
| API SG | | X |
| API SH | | X |

| This product is recommended for use in applications requiring: | MOBIL MONOGRADO 40 | MOBIL MONOGRADO 50 |
|--|--------------------|--------------------|
| API SG | X | |
| API SH | X | |

| This product meets or exceeds the requirements of: | MOBIL MONOGRADO 40 | MOBIL MONOGRADO 50 |
|--|--------------------|--------------------|
| API SJ | X | X |
| API SL | X | X |

Properties and Specifications

| Property | MOBIL MONOGRADO 40 | MOBIL MONOGRADO 50 |
|----------|--------------------|--------------------|
| Grade | SAE 40 | SAE 50 |

| Property | MOBIL MONOGRADO 40 | MOBIL MONOGRADO 50 |
|--|--------------------|--------------------|
| Density @ 15 C, g/ml, ASTM D1298 | 0.892 | |
| Density @ 15 C, g/ml, ASTM D4052 | 0.896 | 0.901 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 270 | 277 |
| Flash Point, Pensky-Martens Closed Cup, °C, ASTM D93 | 218 | |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 14.8 | 19.6 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 150.7 | 214 |
| Pour Point, °C, ASTM D97 | -17 | -27 |

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

ExxonMobil

Exxon Mobil Esso XTO ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved