



## Mobil Multi-Vehicle ATF

Mobil Passenger Vehicle Lube , Barbados

Automatic Transmission Fluid

### Product Description

Mobil Multi-Vehicle ATF is a premium synthetic blend lubricant formulated for use in a wide variety of North American, European, and Asian vehicles.

### Features and Benefits

Advantages offered by Mobil Multi-Vehicle ATF over transmission fluids of lower quality are:

- Long fluid life and long transmission life
- Exceptional oxidation stability and resistance to chemical deterioration
- Excellent flow properties at low start-up temperatures and high operating temperatures
- Excellent lubricating characteristics for quiet operation, smooth shifting, and excellent wear protection
- Excellent viscosity stability (high viscosity index) to help assure adequate lubrication without excessive thinning in severe high-temperature service or thickening at low starting temperatures
- Dependable protection against rust and corrosion

### Applications

Mobil Multi-Vehicle ATF is a premium lubricant for car and truck automatic transmissions and other applications & recommended by ExxonMobil for use in applications that require an automatic transmission fluid satisfying Ford Mercon and Mercon V performance levels.

Recommended by ExxonMobil for use in applications requiring Dexron III.

Good maintenance practice dictates that automatic transmissions be checked for proper fluid levels at regular intervals, and that the fluid be drained and replaced at intervals recommended by the manufacturer. Some manufacturers recommend more frequent changes of transmission fluid under severe driving conditions such as those that occur in heavy traffic, in hot weather, or when pulling a trailer.

### Specifications and Approvals

<b>This product is recommended for use in applications requiring:</b>
Ford MERCON
GM DEXRON
GM DEXRON II
GM DEXRON IID
GM DEXRON IIE
GM DEXRON IIIG
GM DEXRON IIIH

**This product is recommended for use in applications requiring:**

JASO 1-A

VOLVO 97340

ALLISON C-4

**This product meets or exceeds the requirements of:**

Ford MERCON V

**Properties and Specifications**

Property	
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	7.42
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	34.1
Viscosity Index, ASTM D2270	193
Flash Point, Cleveland Open Cup, °C, ASTM D92	180
Color, Visual	Red

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024




© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved