



DIOL RD 13 RD 40 and 17 RD 40

Mobil Commercial Vehicle Lube , Bangladesh

Premium Railroad Engine Oils

Product Description

DIOL RD 13 RD 40 and 17 RD 40 oils are premium crankcase lubricants for locomotive diesel engines. These products are designed to meet the severe service demands imposed by newer railroad diesel locomotive engines. Each is formulated using high quality base oils and an additive package endorsed by equipment builders and the applicable requirements of General Electric (GE) and Electromotive Diesel (EMD) for their modern engines.

Features and Benefits

LMOA Generation 5 is the latest and most demanding quality for diesel locomotive engines. A Generation 5 oil must incorporate improved additive technology to meet the high demands of extended oil drain intervals. Increased levels of insolubles must be well dispersed in the lube oil to minimize wear. At the same time, effective oxidation control must be maintained. The results of using such a lubricant are:

- Cleaner engines due to reduced deposits
- Reduced maintenance due to extended drain intervals

DIOL RD Series products incorporate additive technology designed for LMOA Generation 5 performance. They also meet the requirements of GE Generation 4 Locomotive oil specification and are posted on the Internal Listings of GE and EMD. Furthermore, DIOL RD Series products are zinc free, low chlorine, and non-corrosive to bearings and other engine metals.

Applications

Diesel locomotive engines specifying LMOA Generation 5 operating with extended drains

Specifications and Approvals

This product has the following approvals:	DIOL 13 RD 40	DIOL 17 RD 40
EMD Domestic Common Additive Approach (recognition ltr on file)	X	
EMD Worthy of Field Test (recognition letter on file)	X	
GE Gen 4 LL - Fundamental Approval (letter on file)	X	
GE Transportation, A Wabtec Company LMOA Gen 4 LL - Fundamental Approval (letter on file)		X

Properties and Specifications

Property	DIOL 13 RD 40	DIOL 17 RD 40
Grade	SAE 40	SAE 40
Ash, Sulfated, mass%, ASTM D874	1.5	2
Chlorine, ppm, ASTM D6443	25	30
Density @ 15 C, kg/l, ASTM D4052	0.89	0.89

Property	DIOL 13 RD 40	DIOL 17 RD 40
Flash Point, Cleveland Open Cup, °C, ASTM D92	284	264
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	14.8	14.8
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	146	142
Pour Point, °C, ASTM D97	-15	-15
Total Base Number, mgKOH/g, ASTM D2896	13.2	17.2
Viscosity Index, ASTM D2270	101	103
Zinc, mg/kg, ASTM D5185	<10	<10

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

MJL Bangladesh Limited

Mobil House, CWS (A) 13/A, Gulshan Avenue,

Bir Uttam Mir Shawkat Sarak, Dhaka-1212, Bangladesh.

Tel: +880258815895, Hot Line: 16669

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTD

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved