



Mobil DTE™ 20 ZF Series

Mobil Industrial , Bangladesh
Hydraulic Oil

Product Description

Mobil DTE™ 20 ZF Series oils are superior hydraulic oils specifically designed to meet the needs of modern, high pressure, industrial and mobile equipment hydraulic systems. They are formulated from high quality base stocks and specially selected zinc free additives. This unique additive system was developed to give excellent protection due to excellent anti-wear performance in severe hydraulic applications.

The Mobil DTE 20 ZF oils exhibit excellent oxidation and thermal stability properties which can help to provide extended oil and filter life, as well as optimum equipment protection, thereby reducing both maintenance and product disposal costs. They are designed to work with systems operating under moderate to severe conditions where high levels of anti-wear and film strength protection are needed.

Features and Benefits

The Mobil DTE 20 ZF Series hydraulic oils exhibit excellent oxidation resistance and thermal stability characteristics that can lead to extension of oil and filter change intervals and help to provide clean systems and trouble-free operation. Their high level of anti-wear properties and excellent film strength characteristics can improve equipment performance that can not only result in fewer breakdowns, but also can help to enhance productivity. Their outstanding demulsibility permits the oils to perform well in systems contaminated with small amounts of water, and readily separate large amounts of water.

| Features | Advantages and Potential Benefits |
|--|---|
| Thermal and Oxidation Stability | Provides long oil and equipment life |
| Anti-wear Properties | Helps reduce wear and protects pumps and components for extended equipment life |
| Excellent Demulsibility Characteristics | Protects systems where small quantities of moisture are present |
| Multi Metal Compatibility | Helps ensure excellent performance and protection with a wide variety of component metallurgy |
| Meets a Wide Range of Equipment Requirements | Minimizes inventory requirements |

Applications

- Systems employing multi-metal designs in pumps and other system components
- Applications where cross-contamination of hydraulic fluids and coolants can occur
- High pressure vane, piston and gear pumps
- Where small amounts of water are unavoidable
- In systems containing gears and bearings
- Systems requiring a high degree of load-carrying capability and anti-wear protection

Specifications and Approvals

| This product has the following approvals: | MOBIL DTE 24 ZF | MOBIL DTE 25 ZF | MOBIL DTE 26 ZF |
|---|-----------------|-----------------|-----------------|
| Denison HF-0 | X | X | X |
| Denison HF-1 | X | X | X |

| This product has the following approvals: | MOBIL DTE 24 ZF | MOBIL DTE 25 ZF | MOBIL DTE 26 ZF |
|---|-----------------|-----------------|-----------------|
| Denison HF-2 | X | X | X |
| Eaton E-FDGN-TB002-E | X | X | X |

| This product is recommended for use in applications requiring: | | | |
|--|---|---|--|
| Fives Cincinnati P-68 | X | | |
| Fives Cincinnati P-69 | | | |
| Fives Cincinnati P-70 | | X | |

| This product meets or exceeds the requirements of: | | | |
|--|---|---|---|
| ASTM D6158 (Class HMHP) | X | X | X |
| China GB 11118.1-2011, L-HM(General) | X | X | X |
| DIN 51524-2:2017-06 | X | X | X |
| ISO L-HM (ISO 11158:2009) | X | X | X |
| JCMAS HK VG32 | X | | |
| JCMAS HK VG46 | | X | |

Properties and Specifications

| Property | MOBIL DTE 24 ZF | MOBIL DTE 25 ZF | MOBIL DTE 26 ZF |
|---|-----------------|-----------------|-----------------|
| Grade | ISO 32 | ISO 46 | ISO 68 |
| Density @ 15.6 C, kg/l, ASTM D4052 | 0.857 | 0.864 | 0.871 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 224 | 232 | 242 |
| Foam, Sequence I, Stability, ml, ASTM D892 | 0 | 0 | 0 |
| Foam, Sequence I, Tendency, ml, ASTM D892 | 0 | 0 | 0 |
| Foam, Sequence II, Stability, ml, ASTM D892 | 0 | 0 | 0 |
| Foam, Sequence II, Tendency, ml, ASTM D892 | 0 | 0 | 0 |
| Foam, Sequence III, Stability, ml, ASTM D892 | 0 | 0 | 0 |
| Foam, Sequence III, Tendency, ml, ASTM D892 | 0 | 0 | 0 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 32.72 | 46.26 | 68.33 |
| Pour Point, °C, ASTM D97 | -36 | -36 | -32 |
| Rust Prevention, Procedure B, Rating, ASTM D665 | Pass | Pass | Pass |
| Viscosity Index, ASTM D2270 | 112 | 108 | 102 |

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

MJL Bangladesh Limited

Mobil House, CWS (A) 13/A, Gulshan Avenue,

Bir Uttam Mir Shawkat Sarak, Dhaka-1212, Bangladesh.

Tel: +880258815895, Hot Line: 16669

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved