



Mobil 1™ 0W-40

Mobil Passenger Vehicle Lube , Bangladesh

Advanced Full Synthetic Motor Oil

Product Description

Mobil 1™ is the world's leading synthetic motor oil brand delivering our ultimate performance and protection.

Mobil 1™ 0W-40 Advanced Full Synthetic Motor Oil is engineered for the latest gasoline and diesel (without Diesel Particulate Filters or DPFs) engine technology delivering excellent all-round performance. It provides exceptional cleaning power, wear protection and overall performance. Mobil 1 0W-40 keeps your engine running like new in all driving conditions.

Features and Benefits

Mobil 1™ 0W-40 is made with a proprietary blend of ultra high performance synthetic basestocks fortified with a precisely balanced component system.

- Meets or exceeds the latest OEM and industry approvals
- Is chosen for factory fill in many of the world's finest vehicles
- Provides excellent overall performance
- Has excellent low temperature capabilities for rapid engine protection at start-up
- Has enhanced frictional properties that aids fuel economy
- Delivers fast protection for reduced engine wear and deposits even in the most extreme driving conditions
- Provides exceptional cleaning power for dirty engines

Applications

Thanks to extensive cooperative development work with major manufacturers and the application of the latest lubrication technology, Mobil 1™ 0W-40 is recommended for many types of modern vehicles where it will help provide unsurpassed performance even under very demanding driving conditions.

- Latest engine technologies including Turbo-chargers, Direct Injection, Diesels (without DPF) and Hybrids
- High performance engines
- Most operating conditions, from mild to extreme

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:
MB-Approval 229.3
MB-Approval 229.5
VW 502 00
VW 505 00

This product is recommended for use in applications requiring:

This product is recommended for use in applications requiring:

API CF

FIAT 9.55535-M2

VW 503 01

This product meets or exceeds the requirements of:

API SJ

API SL

API SM

API SN

ACEA A3/B3

ACEA A3/B4

Properties and Specifications

Property	
Grade	SAE 0W-40
Total Base Number, mgKOH/g, ASTM D2896	12.5
Ash, Sulfated, mass%, ASTM D874	1.2
Flash Point, Cleveland Open Cup, °C, ASTM D92	233
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	77
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.6
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	13.5
Density @ 15.6 C, g/ml, ASTM D4052	0.839
Viscosity Index, ASTM D2270	180
Mini-Rotary Viscometer, Apparent Viscosity, -40 C, mPa.s, ASTM D4684	28200
Pour Point, °C, ASTM D97	-45

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

MJL Bangladesh Limited**Mobil House, CWS (A) 13/A, Gulshan Avenue,****Bir Uttam Mir Shawkat Sarak, Dhaka-1212, Bangladesh.**


Tel: +880258815895, Hot Line: 16669

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobilExxon Mobil  

© Copyright 2003-2022 Exxon Mobil Corporation. All
Rights Reserved