



MOBILUBE FE 75W-85

Mobil Passenger Vehicle Lube , Bulgaria

Axle oil

Product Description

Mobilube FE 75W-85 is an Axle oil. This product is a hypoid gear oil suitable for use in Mercedes Benz passenger cars axles and other applications specified by 235.7.

Features and Benefits

Mobilube FE 75W-85 helps to optimize the efficiency of the axles.

Specifications and Approvals

MOBILUBE FE 75W-85 has the following approval:	
MB-approval 235.7	X

Typical Properties

MOBILFLUID FE 75W-85	
Viscosity	
cSt @ 100°C	11.9
cSt @ 40°C	67.9
Viscosity Index	173
Flash Point, °C	200
Pour Point, °C	-42
Density kg/m ³	867

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype and the Pegasus design are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

05-2020

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local

ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved