



Mobil Super™ 1000 X1 20W-50

Mobil Passenger Vehicle Lube , Bahrain

Mobil Passenger Engine Oil

Product Description

The Mobil Super™ 1000 range of lubricants are premium mineral engine oils, designed to provide a high level of protection and performance.

Features and Benefits

Mobil Super 1000 products are industry tested so you can trust you will get the performance you want from your vehicle.

Mobil Super 1000 X1 provides:

- Good wear protection
- Good engine cleanliness
- Good high temperature protection

Applications

Mobil Super 1000 products have been formulated for use in nearly all vehicles. Mobil Super 1000 is suitable for:

- Nearly all engine technologies
- Gasoline and Diesel
- Passenger cars, SUV's, light trucks and vans
- Highway cruising
- Normal Operating Conditions

Mobil Super 1000 X1 20W-50 is also suitable for use in LPG vehicles.

ExxonMobil particularly recommend Mobil Super 1000 for daily driving under normal conditions. Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

| |
|---|
| This product has the following approvals: |
| MB-Approval 229.1 |
| VW 501 01 |
| VW 505 00 |

| |
|--|
| This product is recommended for use in applications requiring: |
| API CF |

| |
|--|
| This product meets or exceeds the requirements of: |
| API SJ |

| |
|--|
| This product meets or exceeds the requirements of: |
| API SL |
| API SM |
| API SN |
| API SN PLUS |
| ACEA A3/B3 |

Properties and Specifications

| Property | |
|---|------------|
| Grade | SAE 20W-50 |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 20.4 |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445 | 181 |
| Density @ 15.6 C, g/ml, ASTM D4052 | 0.886 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 255 |
| Pour Point, °C, ASTM D97 | -27 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.
04-2024

ExxonMobil

Exxon

Mobil

Esso

XTO ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved