



Mobil Special 40, 50

Mobil Passenger Vehicle Lube , Bermuda

Added Performance Engine Oil

Product Description

Mobil Special 40, 50 Series are heavy duty engine oils primarily intended for use in gasoline automotive engines of passenger cars. They are formulated from high quality mineral base oils and an advanced additive system required for combustion engines where an API SL engine oil is recommended. . They contain an effective balance of detergents and dispersants to minimize the formation of sludge and deposits, retain alkalinity (TBN) and reduce wear.

Features and Benefits

- Help promote engine cleanliness.
- Good protection against wear and corrosion.
- Extended intervals between oil drain.
- Low oil consumption.

Applications

Mobil Special 40, 50 Series are recommended for the lubrication of gasoline engines for passenger cars. They can also be used in gear and hydraulic applications if the builder approves the use of monogrades engine oils for these applications.

Specifications and Approvals

This product meets or exceeds the requirements of:	MOBIL SPECIAL 40	MOBIL SPECIAL 50
API SL	X	X

Properties and Specifications

Property	MOBIL SPECIAL 40	MOBIL SPECIAL 50
Grade	SAE 40	SAE 50
Ash, Sulfated, mass%, ASTM D874	0.79	0.79
Flash Point, Cleveland Open Cup, °C, ASTM D92	256	262
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.7	19.5
Pour Point, °C, ASTM D97	-27	-27
Total Base Number, mgKOH/g, ASTM D2896	7.2	

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved