



## MOBIL DELVAC MODERN 15W-40 SUPER DEFENSE V3

Mobil Commercial Vehicle Lube , Bolivia

Mobil commercial-vehicle-lube

### Product Description

MOBIL DELVAC MODERN 15W-40 SUPER DEFENSE V3 is an extra high performance diesel engine oil that provides excellent lubrication of today's diesel engines promoting extended engine life. As a result, this product meets or exceeds the specifications of virtually all major European and American engine manufacturers. This extra high performance has been proven in the field in a wide variety of industries, applications, and mixed fleets.

The advanced chemistry of this product provides outstanding performance in both modern, demanding low-emission diesel engines and older diesel engines operating on low or high sulphur fuel. MOBIL DELVAC MODERN 15W-40 SUPER DEFENSE V3 combines a blend of high performance base stocks with a progressive additive system to provide superior control of oil thickening due to soot build-up and high temperatures as well as outstanding resistance to oxidation, corrosion, and high temperature deposits.

### Features and Benefits

High output, low emission diesel engines significantly increase the demands on engine lubricants. Tighter engine designs reduce oil consumption, resulting in less fresh oil make-up to replenish depleted additives. Top piston fire rings are located higher on the piston bringing the oil film closer to the combustion chamber where higher temperatures increase thermal stress on the lubricant. Increased fuel injector pressure and retarded timing improve fuel burn efficiency, but also increase engine temperatures and increase soot loads. MOBIL DELVAC MODERN 15W-40 SUPER DEFENSE V3 is formulated from high performance base oils and a superior balanced additive system to provide optimum engine performance in modern diesel and gasoline engines as well as older models. The key benefits include:

Features	Advantages and Potential Benefits
High thermal and oxidation stability	Reduced sludge build-up, deposits and viscosity increase
TBN reserves	Deposit control and acid neutralisation
Stay-in-grade shear stability	Wear protection and viscosity control
Advanced detergency/dispersancy	Cleaner engines and longer component life
Improved soot handling	Improved viscosity control and used oil pumpability
Excellent low temperature properties	Start-up wear protection
Component compatibility.	Longer gasket and seal life.
Meets demanding specifications of key OEMs.	One engine oil for mixed fleet operations.

### Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment from leading Japanese, European, and American manufacturers.
- On-highway light and heavy-duty trucking.
- Off-highway industries including: construction, mining, quarrying, and agriculture.
- Mixed fleet applications.

## Specifications and Approvals

**This product has the following approvals:**

MACK EO-M PLUS

MACK EO-N

MTU Oil Category 2

RENAULT TRUCKS RLD-2

VOLVO VDS-3

MB-Approval 228.3

KAMAZ V-8 Euro-3, Euro-4 and Euro-5 engines

Cummins CES 20077

Cummins CES 20078

**This product is recommended for use in applications requiring:**

ACEA A2-96 Issue 3

ACEA B2-98 Issue 2

API CF

API CF-4

API CG-4

CUMMINS CES 20071

CUMMINS CES 20072

MACK EO-M

MAN M 3275-1

RENAULT TRUCKS RLD

VOLVO VDS-2

**This product meets or exceeds the requirements of:**

API CH-4

API SJ

API SL

JASO DH-1-17

**This product meets or exceeds the requirements of:**

Caterpillar ECF-2

API CI-4

Cummins CES 20076

**Properties and Specifications**

Property	
Grade	SAE 15W-40
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.4
Appearance, AMS 1738	Clear & Bright
Ash, Sulfated, mass%, ASTM D874	1.3
Flash Point, °C, ASTM D92	228
Viscosity Index, ASTM D2270	140
Pour Point, °C, ASTM D97	-30
Total Base Number, mgKOH/g, ASTM D2896	11.9
Density @ 15.6 C, kg/l, ASTM D4052	0.88

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2024




© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved