



## Mobil Delvac Legend™ 15W-40 Heavy Duty V2

Mobil Commercial Vehicle Lube , Bolivia

Mobil commercial vehicle lube

### Product Description

Mobil Delvac Legend™ 15W-40 Heavy Duty V2 is a high performance diesel engine oil that provides proven protection of diesel engines operating on and off- highway severe service applications. Mobil Delvac Legend™ 15W-40 Heavy Duty V2 is recommended by ExxonMobil for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

### Features and Benefits

The technology in Mobil Delvac Legend™ 15W-40 Heavy Duty V2 delivers excellent performance in both modern diesel engines as well as older models. The key benefits include:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
TBN reserve	Deposit control
Stay-in-grade shear stability	Reduced oil consumption and wear protection
Excellent detergency/dispersancy	Cleaner engines and longer engine life
Component compatibility	Longer gasket and seal life

### Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment of European, Japanese, and American manufacturers
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying, and agriculture

### Specifications and Approvals

<b>This product meets or exceeds the requirements of:</b>
API CH-4

### Properties and Specifications

<b>Property</b>	
-----------------	--

Property	
Grade	SAE 15W-40
Total Base Number, mgKOH/g, ASTM D2896	8
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	4.13
Viscosity Index, ASTM D2270	136
Density @ 15.6 C, g/ml, ASTM D1298	0.868
Flash Point, Cleveland Open Cup, °C, ASTM D92	222
Pour Point, °C, ASTM D97	-33
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	15
Appearance, AMS 1738	Clear and Bright


### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2023

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved