



Mobil Delvac Modern™ 10W-30 Complete Protection

Mobil Commercial Vehicle Lube , Bolivia

Product Description

Mobil Delvac Modern™ 10W-30 Complete Protection is an extra high performance diesel engine oil that helps extend engine life in severe on and off-highway applications while delivering excellent performance in modern, high-output, low-emission engines including those with Exhaust Gas Recirculation (EGR) and Aftertreatment Systems with Diesel Particulate Filters (DPFs) and Diesel Oxidation Catalysts (DOCs). Mobil Delvac Modern™ 10W-30 Complete Protection is recommended by ExxonMobil for use in a wide range of heavy duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries. It meets or exceeds the requirements of the API CK-4, CJ-4, CI-4 PLUS, CI-4 and CH-4 service categories.

Features and Benefits

Mobil Delvac Modern™ 10W-30 Complete Protection is formulated with optimized base oil and additive technology to provide a strong foundation for oxidation resistance, soot handling and wear control supplemented with excellent piston deposit protection and reduced sludge formation to help long engine life.

Features	Advantages and Potential Benefits
Enhanced soot-viscosity control	Engine efficiency, long engine life and long oil life
Outstanding thermal and oxidative stability	Reduced low temperature sludge build-up and high temperature deposits
Good oil consumption control	Lower oil costs due to less make-up oil during operation
TBN reserves	Improved corrosion protection and long drain intervals
Stay-in-grade shear stability	Maintains viscosity in severe, high temperature service for greater wear protection and long engine life
Enhanced low temperature pumpability	Faster oil flow and reduced wear during engine start-up in low temperatures
Outstanding resistance to corrosive and abrasive wear	Long life of critical wear surfaces
Component compatibility	Long gasket, seal and after treatment device (DPF) life

Applications

Recommended by ExxonMobil for use in:

- On-highway heavy-duty trucking and off-highway including: construction, mining, quarrying, and agriculture.
- On-highway applications operating in both high speed/high load and short haul pick-up/delivery.

Specifications and Approvals

This product has the following approvals:

This product has the following approvals:

Detroit Detroit Fluids Specification 93K222

Detroit Fluids Specification 93K218

Ford WSS-M2C171-F1

Mack EO-O Premium Plus

MACK EOS-4.5

VOLVO VDS-4

VOLVO VDS-4.5

This product is recommended for use in applications requiring:

ACEA E9

This product meets or exceeds the requirements of:

API CH-4

API CI-4

API CI-4 PLUS

API CJ-4

API CK-4

Caterpillar ECF-3

Properties and Specifications

Property	
Grade	SAE 10W-30
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	11.9
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.5
Viscosity Index, ASTM D2270	140
Cold-Cranking Simulator, Apparent Viscosity @ -25 C, mPa.s, ASTM D5293	6370
Pour Point, °C, ASTM D97	-33

Health and safetyHealth and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims>

</psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2024

ExxonMobil



© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved