



## MOBIL DELVAC MODERN 10W-40 FULL PROTECTION

Mobil Commercial Vehicle Lube , Bolivia

Mobil commercial-vehicle-lube

### Product Description

MOBIL DELVAC MODERN 10W-40 FULL PROTECTION is an extra high performance synthetic technology diesel engine oil that helps extend engine life in the most severe on and off-highway applications while delivering outstanding performance in modern, high-output, low-emission engines including those with Exhaust Gas Recirculation (EGR) and Aftertreatment Systems with Diesel Particulate Filters (DPFs) and Diesel Oxidation Catalysts (DOCs). Fully backwards compatible, MOBIL DELVAC MODERN 10W-40 FULL PROTECTION will also deliver the same exceptional performance in older conventional engines. It meets or exceeds the requirements of the API CK-4, CJ-4 service categories as well as key Original Equipment Manufacturer (OEM) requirements.

### Features and Benefits

MOBIL DELVAC MODERN 10W-40 FULL PROTECTION is formulated using synthetic technology and a detergent system to deliver excellent performance in both new and older engines. In addition to assuring excellent control of oil thickening due to soot build-up and TBN retention for long drain intervals, MOBIL DELVAC MODERN 10W-40 FULL PROTECTION advanced technology also provides outstanding resistance to oil consumption, oxidation, corrosive and abrasive wear, and high temperature deposits.

Features	Advantages and Potential Benefits
Excellent soot-viscosity control	Helps to maintain engine efficiency, long engine life and long oil life
Outstanding thermal and oxidative stability	Helps to reduce low temperature sludge build-up and high temperature deposits
Excellent oil consumption control	Helps to lower oil costs due to less make-up oil during operation
Excellent TBN reserves	Helps to improve corrosion protection and to extend drain intervals
Stay-in-grade shear stability	Helps to maintain viscosity in severe, high temperature service for greater wear protection and long engine life
Excellent low temperature pumpability	Fast oil flow and helps to reduce wear during engine start-up in low temperatures
Excellent resistance to corrosive and abrasive wear	Long life of critical wear surfaces
Component compatibility	Long gasket, seal, and after treatment (DPF and DOC) life

### Applications

Recommended by ExxonMobil for use in:

- Heavy Duty Diesel Engines including Euro V/VI and China V/VI(1) modern low emissions vehicles, utilizing technologies such as Diesel Particulate Filter (DPF), Selective Catalytic Reduction (SCR), Continuously Regenerating Traps (CRT), Diesel Oxidation Catalysts (DOC) and Exhaust Gas Recirculation (EGR).
- High-performance diesel applications including turbo-charged designs featuring EGR Technology and diesel applications using older, naturally aspirated conventional designs.
- On-highway heavy-duty trucking and off-highway including: construction, mining, quarrying, and agriculture.

## Specifications and Approvals

<b>This product has the following approvals:</b>	
Detroit Detroit Fluids Specification 93K222	
Detroit Fluids Specification 93K218	
MACK EOS-4.5	
RENAULT TRUCKS RLD-3	
VOLVO VDS-4.5	
Cummins CES 20086	
Cummins CES 20081	
MAN M 3775	
Ford WSS-M2C171-F1	
MB-Approval 228.31	
MTU Oil Category 2.1	

<b>This product is recommended for use in applications requiring:</b>	
MAN M 3575	

<b>This product meets or exceeds the requirements of:</b>	
API CJ-4	
API CK-4	
API SN	
ACEA E7	
ACEA E9	
Caterpillar ECF-3	

## Properties and Specifications

Property	
Grade	SAE 10W-40
Viscosity Index, ASTM D2270	158
Total Base Number, mgKOH/g, ASTM D2896	10

Property	
Pour Point, °C, ASTM D97	-48
Noack Volatility, mass%, ASTM D5800	10
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.11
Flash Point, Cleveland Open Cup, °C, ASTM D92	219
Density @ 15.6 C, g/ml, ASTM D1298	0.862
Ash, Sulfated, mass%, ASTM D874	0.69
Appearance, AMS 1738	Clear and Bright

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2024

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved