



## Mobil Delvac™ Modern 15W-40 Light Commercial

Mobil Commercial Vehicle Lube , Bolivia

Mobil commercial-vehicle-lube

### Product Description

Mobil Delvac™ Modern 15W-40 Light Commercial is an engine oil that provides excellent lubrication of diesel and gasoline engines operating in severe driving conditions typically encountered in city operations. This product is recommended by ExxonMobil for European, Russian and American engines for use in a wide range of traditional light-duty commercial vehicles.

### Features and Benefits

Mobil Delvac™ Modern 15W-40 Light Commercial is formulated from high performance base oils and a superior balanced additive system to provide optimum engine performance in modern diesel and gasoline engines as well as older models. Key benefits include:

Features	Advantages and Potential Benefits
Increased thermal and oxidation stability	Help to reduced sludge build-up, deposits, and long oil and engine life
Enhanced wear protection	Helps towards long component and engine life
Improved corrosion protection	Helps to reduce bearing wear to assist with long drain intervals in modern diesel engines
Advanced piston deposit control	Helps to keep engines clean with reduced maintenance costs and long engine life
Advanced soot handling to control viscosity increase, sludge build up, and filter pressure	Helps to enhance engine protection for long engine life
Enhanced low temperature pumpability	Fast start up with reduced wear operating in low temperature climates

### Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered engines built by European, Russian, and American manufacturers.
- On-highway light trucking including mixed fleets with gasoline engines.
- For GAZ Light Duty Vehicles with diesel or petrol engines requiring API CI-4 or API SL motor oils.

### Specifications and Approvals

This product has the following approvals:
MB 228.3
Cummins CES 20077
Cummins CES 20078

**This product is recommended for use in applications requiring:**

ACEA A2-96 Issue 3

ACEA B2-98 Issue 2

API CF

**This product meets or exceeds the requirements of:**

API CH-4

API CI-4

API SJ

API SL

ACEA E7-16

Caterpillar ECF-2

JASO DH-1

Cummins CES 20076

**Properties and Specifications**

Property	
Grade	SAE 15W-40
Density @ 15.6 C, kg/l, ASTM D4052	0.88
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.4
Ash, Sulfated, mass%, ASTM D874	1.3
Flash Point, °C, ASTM D92	228
Pour Point, °C, ASTM D97	-30
Viscosity Index, ASTM D2270	140
Total Base Number, mgKOH/g, ASTM D2896	11.9
Noack Volatility, mass%, ASTM D5800	11.6
Appearance, AMS 1738	Clear and Bright

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2024

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved