



## Mobil™ Mining Coolant 50%

Mobil Commercial Vehicle Lube , Bolivia

Antifreeze & Coolant

### Product Description

Mobil™ Mining Coolant 50% is a ready-to-use coolant that acts as a corrosion inhibitor, antifreeze and anti-boil with stabilizers and foam suppressants in heavy-duty cooling systems. a blend of monoethylene glycol, deionized water, and a corrosion inhibitor package. Contains nitrite and molybdate in its composition, being free from salts such as nitrate, phosphate, borate and silicate.

### Features and Benefits

Mobil™ Mining Coolant 50% has the following features and benefits:

- Ready to use" refrigerant solution and does not require dilution in the field
- Contains nitrite in the composition to provide excellent protection against cavitation corrosion
- Provides superior protection to all metal alloys in the system, even after an aging period, when conventional inorganic based additives such as silicates and borates lose efficiency and require reinforcing filler
- Ensures good stability and absence of deposits, due to the absence of silicates and phosphates;
- Good stability at high temperatures
- Does not require the addition of supplementary additives (SCA), avoiding errors in the dilution of the mixture
- Minimizes corrosion by cavitation and erosion of the water pump by its foam suppressing property;
- Does not attack elastomers - hoses and gaskets

### Applications

Mobil™ Mining Coolant 50% is indicated as a coolant in mining equipment cooling systems, for a varied fleet of diesel powered heavy vehicles such as trucks, on-highway fleets, agricultural equipment, off-highway equipment, passenger vehicles and pick-ups.

Mobil™ Mining Coolant 50% provides excellent performance with long-lasting corrosion protection in aqueous systems in the presence of multi-metals such as iron, steel, copper, brass, aluminum and its alloys, soft solder and silver solder.

### Meets or Exceeds:

ASTM D3306

ASTM D6210

ASTM D4340

ABNT NBR 13705

Caterpillar CAT ELC - EC-1

Chrysler MS7170 Sec. A&B 1-4

Cummins CES 14603

MTU MTL 5048

Navistar MPAPS B-1

Volvo / Mack Trucks

Mack Truck ELC Coolant

Freighliner 48-22880

TCM RP 329

### Properties and Specifications

Property	
Boiling Point, C, ASTM D1120	108

Property	
Color, Visual	Pink
Foaming at 24 C, Volume, ml, ASTM D892	1.065
Density 20 C, g/ml, ASTM D1122	150
Freeze Point (no dilution), C, ASTM D1177	-37
pH, of Finished Product, ASTM D1287	9.5
Foaming at 24 C, Time, s, ASTM D892	5

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2023

**ExxonMobil**



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved