



Mobil Delvac Legend 1300 Monogrados

Mobil Commercial Vehicle Lube , Caribbean

High Performance Diesel Engine Oils

Product Description

Mobil Delvac Legend TM 1320, 1330, 1340, and 1350 are high performance monograde diesel engine oils formulated from advanced technology base oils balanced additive system. They are specifically engineered for performance in intercooled, turbo-charged engines operating under severe on and off-highway conditions. Mobil Delvac Legend TM 1300 are used in a wide range of applications where a monograde lubricant is recommended.

Features and Benefits

Features	Advantages and Potential Benefits
Excellent protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion	Prolonged engine life Less wear Excellent protection against ring sticking
Extended TBN reserve	Long-term deposit/wear control Controls formation of acids when using higher sulfur fuels

Applications

- Recommended by ExxonMobil for use in:
- Naturally aspirated and turbo-charged diesel powered equipment
 - On highway light and heavy duty trucking
 - Off highway industries including: construction, mining, quarrying, and agriculture
 - Hydraulic system and wet breaks in mobile equipment where a SAE 20 diesel engine oil is required (Mobil Delvac Legend TM 1320)

Specifications and Approvals

This product is recommended for use in applications requiring:	MOBIL DELVAC LEGEND 1320	MOBIL DELVAC LEGEND 1330	MOBIL DELVAC LEGEND 1340	MOBIL DELVAC LEGEND 1350
API CF	X	X	X	X

Properties and Specifications

Property	MOBIL DELVAC LEGEND 1320	MOBIL DELVAC LEGEND 1330	MOBIL DELVAC LEGEND 1340	MOBIL DELVAC LEGEND 1350
Grade	SAE 20	SAE 30	SAE 40	SAE 50
Ash, Sulfated, mass%, ASTM D874	1.22	0.7	0.69	0.2
Flash Point, Cleveland Open Cup, °C, ASTM D92	234	240	262	274

Property	MOBIL DELVAC LEGEND 1320	MOBIL DELVAC LEGEND 1330	MOBIL DELVAC LEGEND 1340	MOBIL DELVAC LEGEND 1350
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	8.2	11.2	14.7	18.8
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	57.7	9.4	144	210
Pour Point, °C, ASTM D97	-27	-27	-24	-24
Total Base Number, mgKOH/g, ASTM D2896	10.2	6.7	6.6	7.4
Viscosity Index, ASTM D2270	110	104	101	99

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2022
ExxonMobil de Colombia S.A.
Calle 90 N° 21-32 , Bogota , Colombia

(571) 628 - 0460

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved