



Mobil Delvac Legend™ CH-4 15W-40 Heavy Duty

Mobil Commercial Vehicle Lube , Caribbean

Mobil commercial-vehicle-lube

Product Description

Mobil Delvac Legend™ CH-4 15W-40 Heavy Duty is a high performance diesel engine oil that provides proven engine protection of diesel engines operating in off-highway severe service applications. Mobil Delvac Legend™ CH-4 15W-40 Heavy Duty is recommended by ExxonMobil for use in a wide range of heavy applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

Features and Benefits

The technology in Mobil Delvac Legend™ CH-4 15W-40 Heavy Duty delivers excellent performance in both modern diesel engines as well as older models. Provides up to an average of 30% more viscosity control¹.

| Features | Advantages and Potential Benefits |
|--|---|
| Provides up to an average of 40% more valve train wear protection ¹ | Longer engine life |
| TBN reserve | Deposit control |
| Stay-in-grade shear stability | Reduced oil consumption and wear protection |
| Excellent detergency/dispersancy | Clean engines and long engine life |
| Thermal and oxidation stability | Controls sludge build-up and deposits |

1. Compared to API CH-4 standard. Based on Sequence IIIF and RFWT engine test.

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment from Chinese, European, Japanese, and American manufacturers.
- On-highway light and heavy-duty trucking.
- Off-highway industries including: construction, mining, quarrying, and agriculture.

Specifications and Approvals

| This product has the following approvals: |
|--|
| MB-Approval 228.3 |
| MTU Oil Category 2 |
| This product meets or exceeds the requirements of: |
| API CH-4 |
| API SJ |

| |
|--|
| This product meets or exceeds the requirements of: |
| Cummins CES 20076 |

Properties and Specifications

| Property | |
|---|------------|
| Grade | SAE 15W-40 |
| Viscosity Index, ASTM D2270 | 137 |
| Pour Point, °C, ASTM D97 | -33 |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445 | 115.9 |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 15.21 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 233 |
| Density @ 15 C, kg/l, ASTM D4052 | 0.87 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024
ExxonMobil de Colombia S.A.
Calle 90 N° 21-32 , Bogota , Colombia

(571) 628 - 0460

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTON

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved