



**MOBIL DELVAC LEGEND 25W50 HIGH MILEAGE**

Mobil Commercial Vehicle Lube , Caribbean

High Performance Diesel Engine Oil

**Product Description**

Mobil Delvac Legend 25W-50 Alta Viscosidad, high performance diesel engine oil that provides proven protection for diesel engines operating in severe service applications. Mobil Delvac 25W-50 Alta Viscosidad is recommended for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

**Features and Benefits**

More than 90 year of experience and innovation supports the technology in Mobil Delvac Legend 25W-50 Alta Viscosidad. Delivers excellent performance in both naturally aspirated as well as turbo-charged diesel powered equipment. The key benefits include:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
TBN reserve	Deposit control and acid neutralization
High Viscosity and Stay-in-grade shear stability	Reduced oil consumption, increased wear protection and high oil pressure across a wide operating temperature range
Excellent detergency/dispersancy	Cleaner engines and prolonged engine life
Component compatibility	Long gasket and seal life

**Applications**

- Naturally aspirated and turbo-charged diesel powered equipment European, Japanese, and American manufacturers
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying, and agriculture

**Specifications and Approvals**

<b>This product is recommended for use in applications requiring:</b>
API CF-4

**Properties and Specifications**

Property	
Grade	SAE 25W-50

Property	
Viscosity Index, ASTM D2270	116
Flash Point, Cleveland Open Cup, °C, ASTM D92	250
Density @ 15 C, g/ml, ASTM D1298	0.89
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	18.7
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	181.5
Pour Point, °C, ASTM D97	-27

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2020

ExxonMobil de Colombia S.A.

Calle 90 N° 21-32 , Bogota , Colombia



(571) 628 - 0460

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**

Exxon Mobil  

© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved