



Mobil Super 2000 5W-30 and 10W-30

Mobil Passenger Vehicle Lube , Caribbean

Premium Semi-Synthetic Passenger Vehicle Engine Oil

Product Description

Mobil Super 2000 5W-30 and 10W-30 are enhanced-premium semi-synthetic motor oils meeting the latest industry engine oil specifications. They are designed to provide an excellent level of protection and performance under the most demanding conditions.

Features and Benefits

Mobil Super 2000 products are industry proven so you can trust you will get the performance you want from your vehicle. Mobil Super 2000 5W-30 and 10W-30 contain low friction semi-synthetic formulation which increases engine efficiency and offers greater fuel economy. Mobil Super 2000 5W-30 and 10W-30 helps to promote long engine life.

Mobil Super 2000 provides:

- Thanks to its semi-synthetic formulation provides improved fuel economy up to a 3%* by enabling the engine to work more efficiently
- Its additive package provides excellent protection against engine wear and deposit formation.
- Provides superior engine protection during start up
- Excellent high temperature protection thanks to its high quality base oil formulation

Applications

Mobil Super 2000 5W-30 and 10W-30 products are formulated to give you confidence of protection beyond that of conventional oils. We particularly recommend it for the following vehicle types and conditions:

- Latest gasoline engine technologies
- Passenger cars, SUV's, light trucks and vans
- Stop and Go City Driving
- Normal to severe operating conditions
- Turbo-Chargers
- High Performance Engines

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product is recommended by ExxonMobil for use in applications requiring:	5W-20	5W-30	5W-40	10W-30
API CF			X	

This product is recommended for use in applications requiring:	5W-20	5W-30	5W-40	10W-30
API CF	X	X		
API Energy Conserving (SM)		X		X
ILSAC GF-4	X	X		X

This product meets or exceeds the requirements of:	5W-20	5W-30	5W-40	10W-30
API SJ		X		X
API SL		X		X
API SM	X	X	X	X
API SN	X	X	X	X
API SN Resource Conserving		X		X
ILSAC GF-5	X	X		X
Chrysler MS-6395		X		

Properties and Specifications

Property	5W-20	5W-30	5W-40	10W-30
Grade	SAE 5W-20	SAE 5W-30	SAE 5W-40	SAE 10W-30
Ash, Sulfated, mass%, ASTM D874	0.8	0.8	0.8	0.82
Density @ 15 C, g/ml, ASTM D4052	0.85	0.86	0.86	0.8665
Flash Point, Cleveland Open Cup, °C, ASTM D92	220	220	220	220
Hi-Temp Hi-Shear Viscosity @ 150 C, mPa.s, ASTM D4683			3.7	
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	2.6			3.14
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	8.5	10.5	14	10.4
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	48	62	85	66.3
Pour Point, °C, ASTM D97	-30	-33	-33	-33
Viscosity Index, ASTM D2270	155	160	170	145

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2020

ExxonMobil de Colombia S.A.

Calle 90 N° 21-32 , Bogota , Colombia

(571) 628 - 0460

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is

intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved