



Mobil Super™ 4T 10W-30, 10W-40, 15W-40, 20W-40, 15W-50 and 20W-50

Mobil Passenger Vehicle Lube , Caribbean

High Performance Four-Stroke Motorcycle Engine Oil

Product Description

Mobil Super™ 4T 10W-30, 10W-40, 15W-40, 20W-40, 15W-50 and 20W-50 are high performance conventional four-stroke motorcycle engine oils primarily intended for general use in all types of four-stroke motorcycles and engines.

Features and Benefits

Mobil Super 4T 10W-30, 10W-40, 15W-40, 20W-40, 15W-50 and 20W-50 combine highly refined, quality mineral oils and an advanced additive system to provide good engine cleanliness, good wear protection and corrosion protection. Key features and benefits include:

| Features | Advantages and Potential Benefits |
|---------------------------------|---|
| Good wear protection | Helps extend engine life |
| Thermal and oxidation stability | Helps keep engines clean for smoother operation |
| Good corrosion protection | Protects critical engine components |
| Broad viscosity range | Year round engine protection and performance |

Specifications and Approvals

| Mobil Super 4T meets or exceeds the requirements of: | 10W-30 | 10W-40 | 15W-40 | 20W-40 | 15W-50 | 20W-50 |
|--|--------|--------|--------|--------|--------|--------|
| API | | | SJ | | | SJ |
| JASO | MA2 | MA2 | MA2 | MA2 | MA2 | MA2 |

| Mobil Super 4T is recommended by ExxonMobil for use in applications requiring: | 10W-30 | 10W-40 | 15W-40 | 20W-40 | 15W-50 | 20W-50 |
|--|--------|--------|--------|--------|--------|--------|
| API | SG | SG | SG | SG/CD | SG/CD | SG |

Typical Properties

| Mobil Super 4T | 10W-30 | 10W-40 | 15W-40 | 20W-40 | 15W-50 | 20W-50 |
|------------------------------|--------|--------|--------|--------|--------|--------|
| SAE Grade | 10W-30 | 10W-40 | 15W-40 | 20W-40 | 15W-50 | 20W-50 |
| Viscosity, ASTM D445 | | | | | | |
| cSt @ 40°C | 70 | 100 | 108 | 118 | 165 | 167 |
| cSt @ 100°C | 10.8 | 14.5 | 14.5 | 14 | 16.8 | 18.8 |
| Sulfated Ash, wt%, ASTM D874 | 0.96 | 0.91 | 0.99 | 0.85 | 0.97 | 0.96 |
| Pour Point, °C, ASTM D97 | -30 | -30 | -27 | -27 | -36 | -24 |
| Flash Point, °C, ASTM D92 | 226 | 222 | 223 | 230 | 224 | 242 |

| Mobil Super 4T | 10W-30 | 10W-40 | 15W-40 | 20W-40 | 15W-50 | 20W-50 |
|----------------------------------|--------|--------|--------|--------|--------|--------|
| Density @15.6°C g/ml, ASTM D4052 | 0.87 | 0.86 | 0.88 | 0.89 | 0.86 | 0.89 |

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Super 4T are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

05-2020

ExxonMobil de Colombia S.A.

Calle 90 N° 21-32 , Bogota , Colombia

(571) 628 - 0460

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved