



Mobil 1™ ESP 0W-30

Mobil Passenger Vehicle Lube , Caribbean

Advanced Synthetic Motor Oil

Product Description

Mobil 1™ ESP 0W-30 is an advanced synthetic engine oil designed to help provide exceptional cleaning power, wear protection and overall performance. Mobil 1 ESP 0W-30 has been expertly engineered to help prolong the life and maintain the efficiency of emission systems in both diesel and gasoline powered automobiles. Mobil 1 ESP 0W-30 meets or exceeds the requirements of many leading industry and car manufacturers' standards required for newer modern diesel and gasoline powered passenger car engines.

Features and Benefits

Mobil 1 ESP 0W-30 is made with a proprietary blend of leading edge components formulated to be fully compatible with the latest Diesel Particulate Filters (DPF's) and Gasoline Catalytic Converters (CAT's). Mobil 1 ESP 0W-30 has been designed to help deliver outstanding performance and protection in conjunction with potential fuel economy benefits. Key features and potential benefits include:

| Features | Advantages and Potential Benefits |
|--|---|
| Low Ash Content | Helps to reduce particulate build up in Diesel Particulate Filters |
| Low Sulfur and Phosphorous content | Helps to reduce poisoning of Gasoline Catalytic Converters |
| Active cleaning agents | Helps to reduce deposits and sludge build-up to enable long and clean engine life |
| Enhanced frictional properties | Potentially aids fuel economy |
| Excellent low temperature capabilities | Quick cold weather starting and ultra-fast protection Helps to extend engine life |

Applications

Mobil 1 ESP 0W-30 is recommended for many types of modern automobile engines, especially the high-performance gasoline and diesel engines found in the latest passenger cars, SUVs and light vans.

Mobil 1 ESP 0W-30 is especially suitable for extreme conditions, where conventional oil often may not perform. It is not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.

Specifications and Approvals

| This product has the following approvals: |
|---|
| MB-Approval 229.31 |
| MB-Approval 229.51 |
| MB-Approval 229.52 |
| Porsche C30 |

This product has the following approvals:

VW 504 00

VW 507 00

This product is recommended for use in applications requiring:

Recommended by ExxonMobil for applications requiring ACEA C2

This product meets or exceeds the requirements of:

ACEA C3

API SL

API SN Engine Test Requirements

API SN PLUS ENGINE TEST REQUIREMENTS

API SP ENGINE TEST REQUIREMENTS

Properties and Specifications

| Property | |
|--|-----------|
| Grade | SAE 0W-30 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 12.0 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 63 |
| Density @ 15.6 C, g/ml, ASTM D4052 | 0.845 |
| Pour Point, °C, ASTM D97 | -51 |
| Flash Point, °C, ASTM D92 | 230 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

ExxonMobil de Colombia S.A.

Calle 90 N° 21-32 , Bogota , Colombia

(571) 628 - 0460

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved