



MOBIL DELVAC FF MB 225.25 15W-40

Mobil Commercial Vehicle Lube , Brazil

Mobil commercial-vehicle-lube

Product Description

MOBIL DELVAC FF MB 225.25 15W-40 is an advanced diesel engine oil that helps extend engine life, allowing you to run your business with confidence. Fully backward compatible, MOBIL DELVAC FF MB 225.25 15W-40 delivers exceptional performance in both newer and older heavy duty engine designs.

This oil meets or exceeds the requirements of API CK-4, CJ-4, CI-4 PLUS, CI-4 and CH-4 service categories, as well as key OEM requirements. MOBIL DELVAC 225.25 15W-40 is universal, meaning it may also be used in gasoline engines requiring the API SN specification.

MOBIL DELVAC FF MB 225.25 15W-40 is a tailored formulation that delivers excellent wear and engine protection, extended drain capability, outstanding temperature performance and engine cleanliness. Developed in close collaboration with major OEMs, MOBIL DELVAC FF MB 225.25 15W-40 is recommended for a wide range of heavy duty applications and operating environments in the trucking, mining, construction, agricultural and marine industries.

Features and Benefits

MOBIL DELVAC FF MB 225.25 15W-40 is formulated with optimized base oil technology, containing hydro-processed base stocks and a tailored additive system to deliver extended performance for up to 50% beyond OEM-recommended oil drain intervals.

This proprietary formulation delivers excellent wear protection, superior oxidation stability, and outstanding TBN retention. MOBIL DELVAC FF MB 225.25 15W-40 provides outstanding resistance to oil consumption, oxidation, corrosive and abrasive wear, and high temperature deposits.

Features	Advantages and Potential Benefits
Meets demanding specifications of key OEMs and latest API gasoline service category	One engine oil for mixed fleet operations
Superior oxidation stability	Extended ODI capability. Reduced low temperature sludge build-up and high temperature deposits
Excellent soot and viscosity control	Greater engine efficiency, long engine life and long oil life
Excellent oil consumption control	Lower oil costs due to less make-up oil during operation
Outstanding TBN reserves	Corrosion protection and extended drain intervals for both new and old engines using 500 ppm sulfur diesel fuel
Low temperature fluidity and pumpability	Formulated for smooth starting in cold weather
Resistance to corrosive and abrasive wear	Long life of critical wear surfaces
Component compatibility	Long gasket and seal life
Low ash formulation meeting API CK-4 and CJ-4 requirements	Long emissions aftertreatment life (DPF, DOC and SCR)

Applications

- Recommended for the latest heavy duty diesel engines, including those equipped with aftertreatment systems and EGR.
- Recommended for diesel applications using older and naturally aspirated conventional designs.
- On-highway heavy-duty trucking and off-highway applications including trucking, mining, construction, agriculture and marine.

- On-highway applications operating in both high speed/high load and short haul pick-up/delivery service.
- Off-highway applications operating in severe low speed/heavy load conditions using up to 500 ppm sulfur fuels.
- High performance gasoline engines requiring API SN and mixed fleet operations.
- Diesel-powered equipment from American, European and Japanese OEMs.

Properties and Specifications

Property	
Grade	SAE 15W-40
Density @ 15 C, g/ml, ASTM D1298	0.87
Pour Point, °C, ASTM D97	-33
Flash Point, °C, ASTM D92	225
Total Base Number, mgKOH/g, ASTM D4739	9.4
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	109
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	14
Viscosity Index, ASTM D2270	130

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>  
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2020  
Cosan Lubrificantes e Especialidades S.A.  
Praia da Ribeira, 01  
21930-080 Rio de Janeiro – RJ – BRASIL  
Tel: 0800 644 1562

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)  
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved