



## Mobil Delvac 1340 F2

Mobil Commercial Vehicle Lube , Brazil

High Performance Diesel Engine Oil

### Product Description

Mobil Delvac 1340 F2 is a high performance monograde diesel engine oil formulated from advanced technology base oils and a balanced additive system. It is specifically engineered for performance in intercooled, turbo-charged engines operating under severe on and off-highway conditions. Also used in some commercial vehicles manual transmissions.

### Features and Benefits

Features	Advantages and Potential Benefits
Excellent protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion	Prolonged engine life, Less wear, Excellent protection against ring sticking
Extended TBN reserve	Long-term deposit/wear control, Controls formation of acids when using higher sulfur fuels

### Applications

Recommended by ExxonMobil for use in:

Naturally aspirated and turbo-charged diesel powered equipment.

On highway light and heavy duty trucking.

Off highway industries including: construction, mining, quarrying, and agriculture. Commercial vehicles manual transmissions according to DTFR 13B120.

### Specifications and Approvals

This product has the following approvals:
Daimler Truck DTFR 13B120

This product is recommended for use in applications requiring:
API CF
API SF

### Properties and Specifications

Property	
Grade	SAE 40

Property	
Appearance, AMS 1738	Clear and Bright
Flash Point, Cleveland Open Cup, °C, ASTM D92	264
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.7
Viscosity Index, ASTM D2270	100
Total Base Number, mgKOH/g, ASTM D2896	10
Pour Point, °C, ASTM D97	-30

## Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2024

Cosan Lubrificantes e Especialidades S.A.

Praia da Ribeira, 01


21930-080 Rio de Janeiro – RJ - BRASIL

Tel: 0800 644 1562

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved