



MOBIL DELVAC LEGEND AXLE OIL SERIES

Mobil Commercial Vehicle Lube , Brazil

Mobil Commercial-Vehicle-Lube Heavy Duty Automotive Gear Lubricants

Product Description

Mobil Delvac Legend Axle Oil 80W-90 and Mobil Delvac Legend Axle Oil 85W-140 are high performance, heavy duty gear lubricants formulated from high performance base oils and an advanced additive system. These lubricants are engineered for automotive applications including heavy duty axles and final drives where extreme pressures and shock loading are expected. They are recommended by ExxonMobil for applications where API GL-5 service is required.

Features and Benefits

Today's heavy equipment applications place higher performance demands on drive train lubricants. Higher speeds, higher torque and heavier loads require improved formulations to maximize equipment life and optimize operating costs. Longer service intervals place additional demands on the gear lubricant requiring effective basestock and additive systems. Mobil Delvac Legend Axle Oil 80W-90 and 85W-140 gear lubricants are engineered to meet these challenges. The key benefits include:

Features	Advantages and Potential Benefits
Exceptional thermal stability and resistance to high temperature oxidation	Extended gear and bearing life due to minimal deposits. Longer seal life
Outstanding protection against low speed/high torque wear and against high speed scoring	Increased load carrying capability. Reduced maintenance costs and longer equipment life
Excellent rust and corrosion protection	Reduced wear and longer component life
Effective low temperature lubrication	Improved startability
Compatible with typical automotive seals and gaskets	Minimum leakage and reduced contamination

Applications

Recommended by ExxonMobil for use in:

- Heavy duty axles and final drives requiring API GL-5 level performance
- Passenger cars, on highway light and heavy duty trucks and commercial vehicles
- Off highway industries including: construction, mining, quarrying and agriculture
- Other heavy duty industrial and automotive applications involving hypoid gears operating under conditions where high speed/shock load, high speed/low torque, and/or low speed/high torque prevail

Specifications and Approvals

This product meets or exceeds the requirements of:	MOBIL DELVAC LEGEND AXLE OIL 80W-90 V1	MOBIL DELVAC LEGEND AXLE OIL 85W-140
API GL-5	X	X

Properties and Specifications

Property	MOBIL DELVAC LEGEND AXLE OIL 80W-90 V1	MOBIL DELVAC LEGEND AXLE OIL 85W-140
Grade	SAE 80W-90	SAE 85W-140
Density @ 15.6 C, g/ml, ASTM D4052	0.897	0.9098
Flash Point, Cleveland Open Cup, °C, ASTM D92	212	226
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.47	27.39
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	130	377
Pour Point, °C, ASTM D97	-27	-24
Viscosity Index, ASTM D2270	110	98

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2024

Cosan Lubrificantes e Especialidades S.A.

Praia da Ribeira, 01


21930-080 Rio de Janeiro – RJ - BRASIL

Tel: 0800 644 1562

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved