



Mobil Super™ 2000 X3 10W-40

Mobil Passenger Vehicle Lube , Brazil

Premium Semi-Synthetic Passenger Vehicle Engine Oil - Everyday Protection

Product Description

Mobil Super™ 2000 X3 10W-40 is a semi-synthetic engine oil that provides everyday protection to ensure long engine life.

Features and Benefits

Mobil Super 2000 products are industry proven, so you can trust your engine will get the protection it needs. Mobil Super 2000 X3 10W-40, confidence in every jc provides multiple benefits:

- Very good sludge prevention
- Very good engine cleanliness
- Very good high temperature protection
- Very good wear protection
- Very good cold start-up

Applications

ExxonMobil recommends Mobil Super 2000 X3 10W-40 for:

- Older engine technologies
- Gasoline, Ethanol and CNG engines.
- Passenger cars, SUV's, light trucks and vans
- Highway cruising and stop-and-go city driving
- Normal to occasionally severe operating conditions

Specifications and Approvals

This product meets or exceeds the requirements of:
API SL
API SM
API SN
API SN PLUS
API SP

Properties and Specifications

Property	
Grade	SAE 10W-40
Pour Point, °C, ASTM D97	-33
Flash Point, Cleveland Open Cup, °C, ASTM D92	221
Ash, Sulfated, mass%, ASTM D874	0.8
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	90.8
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	13
Density @ 15.6 C, g/ml, ASTM D4052	0.8681
Viscosity Index, ASTM D2270	142

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2022
Cosan Lubrificantes e Especialidades S.A.
Praia da Ribeira, 01
21930-080 Rio de Janeiro – RJ – BRASIL
Tel: 0800 644 1562

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved