



Mobil Super Moto™ Scooter MX 10W-30

Mobil Passenger Vehicle Lube , Brazil

Semi-Synthetic

Product Description

Mobil Super Moto™ Scooter MX 10W-30 is a high performance, synthetic blend technology four-stroke Scooter engine oil developed for modern Scooters.

Features and Benefits

Mobil Super Moto™ Scooter MX 10W-30 provides better protection than industry standard of API SL. Mobil Super Moto™ Scooter MX 10W-30 is specially designed to smooth acceleration required in city traffic conditions with minimal vibrations.

Features	Advantages and Potential Benefits
Excellent wear protection	Longer engine component and overall engine life
Good thermal, oxidation stability and deposit control	Cleaner running engines resulting in smooth flawless operation
Excellent corrosion protection properties	Longer life of valve train and bearing components
Enhanced low temperature properties	Easier cold weather starting, longer electrical system life
Low friction in engine moving parts	Smooth accelerations and low vibrations

Applications

Mobil Super Moto™ Scooter MX 10W-30 protects modern scooters with automatic transmission, specially protecting high power scooter engine.

Specifications and Approvals

This product meets or exceeds the requirements of:
API SL
JASO MB

Properties and Specifications

Property	
Grade	SAE 10W-30
Ash, Sulfated, mass%, ASTM D874	0.83
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	10.9
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	72.3

Property	
Flash Point, Cleveland Open Cup, °C, ASTM D92	241
Density @ 15 C, g/ml, ASTM D1298	0.863
Pour Point, °C, ASTM D97	-39

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2020

Cosan Lubrificantes e Especialidades S.A.

Praia da Ribeira, 01

21930-080 Rio de Janeiro – RJ - BRASIL

Tel: 0800 644 1562

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO
ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved