



Mobil Super 2000 X2 5W-30

Mobil Passenger Vehicle Lube , Brazil

Premium Semi-Synthetic Passenger Vehicle Engine Oil

Product Description

The Mobil Super 2000 X2 5W-30 lubricant is an enhanced-premium semi-synthetic engine oils, designed to provide an excellent level of protection and performance.

Features and Benefits

Mobil Super 2000 X2 5W-30 product is an industry proven so you can trust you will get the performance you want from your vehicle.

Mobil Super 2000 X2 5W-30 provides:

- Excellent wear protection
- Excellent engine cleanliness
- Excellent high temperature protection
- Fuel economy

Applications

Mobil Super 2000 X2 5W-30 product is formulated to give you confidence of protection beyond that of conventional oils. We particularly recommend it for the following vehicle types and conditions:

- Stop and Go City Driving
- Latest engine technologies
- Gasoline, Ethanol and Diesel
- Passenger cars, SUV's, light trucks and vans
- Highway cruising
- Normal to occasionally severe operating conditions
- Turbo-Chargers
- High Performance Engines

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product is recommended for use in applications requiring:

API CF

Ford WSS-M2C915-A

Ford WSS-M2C929-A

This product is recommended for use in applications requiring:

Ford WSS-M2C946-A

This product meets or exceeds the requirements of:

API SN

API SN PLUS

API SP

ILSAC GF-6A

Properties and Specifications

Property	
Grade	SAE 5W-30
Appearance, AMS 1738	Clear & Bright
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	10.5
Flash Point, Cleveland Open Cup, °C, ASTM D92	225
Pour Point, °C, ASTM D97	-42
Viscosity Index, ASTM D2270	158

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2021

Cosan Lubrificantes e Especialidades S.A.

Praia da Ribeira, 01

21930-080 Rio de Janeiro – RJ - BRASIL

Tel: 0800 644 1562

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved