



## MOBIL TL 52553 X1 5W-40

Mobil Passenger Vehicle Lube , Brazil

Full Synthetic Engine Oil

### Product Description

MOBIL TL 52553 X1 5W-40 is a full synthetic motor oil tailored for smoother acceleration and provides outstanding engine wear protection even under the most demanding driving conditions.

### Features and Benefits

MOBIL TL 52553 X1 5W-40 provides:

- Enhanced high temperature protection
- Enhanced cold start-up performance
- Enhanced engine cleanliness and sludge prevention
- Enhanced wear protection

### Applications

MOBIL TL 52553 X1 5W-40 is formulated to give you confidence of protection beyond that of conventional or semi-synthetic oils. ExxonMobil recommends MOBIL TL 52553 X1 5W-40 if you regularly experience demanding conditions where it can help combat the damage caused by frequent high engine stress:

- Many engine technologies
- Gasoline and Diesel without Diesel Particulate Filters (DPF)
- Passenger cars, SUV's, light trucks and vans
- Highway cruising and stop and go city driving
- High Performance Engines
- Normal to frequently severe operating conditions
- Turbo-Chargers and Direct Injection engines

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

**This product has the following approvals:**

VW 509 99

VW 508 88

**This product meets or exceeds the requirements of:**

API SN

ACEA A3/B4-16

### Properties and Specifications

Property	
Grade	SAE 5W-40
Pour Point, °C, ASTM D97	-33
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	13.3
Appearance, AMS 1738	Clear and Bright
Noack Volatility, mass%, ASTM D5800	10.4
Flash Point, Cleveland Open Cup, °C, ASTM D92	216
Ash, Sulfated, mass%, ASTM D874	1.4
Total Base Number, mgKOH/g, ASTM D2896	11.5
Density @ 15.6 C, g/ml, ASTM D4052	0.8534
Viscosity Index, ASTM D2270	175

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2021

Cosan Lubrificantes e Especialidades S.A.

Praia da Ribeira, 01

21930-080 Rio de Janeiro – RJ - BRASIL

Tel: 0800 644 1562

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved