



Mobil™ ATF Multiveículo

Mobil Passenger Vehicle Lube , Brazil

Mobil passenger-vehicle-lube

Product Description

Mobil ATF Multiveiculo is a premium fully synthetic lubricant formulated from selected high-quality synthetic base oils combined with an advanced additive : designed to meet the service fill needs of the broadest range of step-type automatic transmissions.

Features and Benefits

Mobil ATF Multiveiculo provides consistent all-weather smooth shifting and lubrication protection of the transmission components to help extend transmission serv and provide a comfortable driving experience.

- Excellent protection of the transmission gears and bearings against wear, rust and corrosion helps preserve the transmission life
- Stable and optimized friction characteristics provide quiet and smooth shift performance for the life of the vehicle
- Excellent flow properties at low start-up temperatures and high operating temperatures for all-weather operability
- Exceptional oxidation and resistance against sludge and deposit formation contributes to long fluid life
- Limited oil consumption from leakage as a result of effective foam control properties and compatibility with seal materials

Applications

ExxonMobil supports Mobil ATF Multiveiculo for service fill use in a broad range of 6 to 8-speed step-type automatic transmissions.

Specifications and Approvals

This product has the following approvals:
FORD Mercon LV
GM Dexron VI

This product meets or exceeds the requirements of:
JASO 1-A-LV-15

Properties and Specifications

Property	
Appearance, AMS 1738	Clear and Bright
Viscosity Index, ASTM D2270	156

Property	
Density @ 15 C, g/ml, ASTM D4052	0.845
Brookfield Viscosity @ -40 C, mPa.s, ASTM D2983	10280
Pour Point, °C, ASTM D97	-54
Flash Point, Cleveland Open Cup, °C, ASTM D92	215
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	5.8
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	28

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2023

Cosan Lubrificantes e Especialidades S.A.

Praia da Ribeira, 01


21930-080 Rio de Janeiro – RJ - BRASIL

Tel: 0800 644 1562

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved