



Mobil Super™ Moto 4T 20W-50

Mobil Passenger Vehicle Lube , Brazil

Premium Multigrade Four-Stroke Motorcycle Engine Oil

Product Description

Mobil Super™ Moto 4T 20W-50 is a premium quality mineral four-stroke motorcycle motor oil. The product is designed to provide protection for use in all types of four-stroke motorcycles and engines under most operating conditions.

Features and Benefits

Mobil Super Moto 4T 20W-50 provides motorcycle engine protection and helps promote long engine life.

- Extended protection against engine wear and deposits formation
- Engine protection during start up
- Helps combat sludge

Applications

Mobil Super Moto 4T 20W-50 has been formulated to be suitable for use in motorcycles requiring an API SL claim, meets and exceeds the requirement of JASO MA. ExxonMobil particularly recommend Mobil Super Moto 4T 20W-50 for daily driving under normal conditions:

- All types of four-stroke motorcycles and engines
- Normal Operating Conditions
- Suitable for use under a wide range of temperature conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product meets or exceeds the requirements of:

API SL

JASO MA

JASO MA2

Properties and Specifications

Property	
Grade	SAE 20W-50
Flash Point, Pensky-Martens Closed Cup, °C, ASTM D93	210
Density @ 15 C, g/ml, ASTM D1298	0.8856

Property	
Ash, Sulfated, mass%, ASTM D874	0.85
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	17.3
Pour Point, °C, ASTM D97	-30
Viscosity Index, ASTM D2270	136

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2022

Cosan Lubrificantes e Especialidades S.A.

Praia da Ribeira, 01

21930-080 Rio de Janeiro – RJ - BRASIL

Tel: 0800 644 1562

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved