



Mobilube™ S 80W-90

Mobil Commercial Vehicle Lube , Belarus

Multi-Purpose Drivetrain Lubricant

Product Description

Mobilube™ S 80W-90 is an extra high performance drivetrain lubricant engineered to provide excellent lubrication for state-of-the-art, heavy duty manual transmission components used in on-highway commercial vehicles and cars. Potential benefits include excellent shifting performance, good low temperature fluidity, and high temperature viscosity retention. Mobilube S 80W-90 provides API GL-4/5 level performance.

Features and Benefits

Today's technology has vastly improved the performance capabilities of on-highway vehicles in terms of load, speed, and control through inno-drivetrain designs. These designs have increased the requirements of components and lubricants to deliver a higher level of performance. For heavy-duty applications, friction control, wear reduction, thermal stability, shear stability, rust and corrosion inhibition, and seal protection are features that must be optimally balanced to contribute to long gear and synchroniser life, smooth shift control, fuel economy, and high load capability over a wide range of applications. Mobilube S 80W-90 delivers outstanding performance in current as well as older units. The key benefits include:

Features	Advantages and Potential Benefits
Outstanding load carrying, anti-wear, and extreme pressure performance	Helps to promote long transmission life.
Excellent prevention of deposits and lacquer formation	Helps to promote long seal life, extended drain, and service intervals
Excellent protection from corrosion of copper and its alloys	Helps to promote long life of synchronisers and smoother shifting performance
Effective thermal and oxidation resistance at high operating temperatures	Helps to promote reduced wear and long component life
Excellent shear stability	Maintains effective viscosity and film strength during severe operation
Good low-temperature fluidity	Easier, smoother shifting and quicker starts

Applications

Recommended by ExxonMobil for use in:

- Cars, on highway light and heavy duty trucks, busses, and vans
- Heavy duty automotive type drivetrains where API GL-4/GL-5 level performance is required

Specifications and Approvals

This product has the following approvals:
Mack GO-J
MAN 341 Typ Z2
MAN 342 Typ M2

This product has the following approvals:	
ZF TE-ML 02B	
ZF TE-ML 05A	
ZF TE-ML 12L	
ZF TE-ML 12M	
ZF TE-ML 16B	
ZF TE-ML 19B	
ZF TE-ML 21A	

This product is recommended for use in applications requiring:	
API GL-4	
MAN 341 Typ E2	
Meritor O76-D	
MIL (US) MIL-PRF-2105E	
ZF TE-ML 08	

This product meets or exceeds the requirements of:	
API GL-5	
API MT-1	
R. Bosch AS TE-ML 08	
ISUZU Axle Oil	
Scania STO 1:0	
ISUZU Large Manual Transmission Oil	
ZF TE-ML 07A	
SCANIA STO 1:1G	

Properties and Specifications

Property	
Grade	SAE 80W-90
Density @ 15 C, g/cm3, ASTM D4052	0.9

Property	
Flash Point, Cleveland Open Cup, °C, ASTM D92	210
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	15
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	144
Pour Point, °C, ASTM D97	-30
Viscosity Index, ASTM D2270	105

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.
11-2023

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved