



## Mobil Delvac™ Light Commercial Vehicle 10W-40

Mobil Commercial Vehicle Lube , Belarus

Superior Engine Protection Light Commercial Vehicle Oil

### Product Description

Mobil Delvac™ Light Commercial Vehicle 10W-40 is an engine oil that provides excellent lubrication of diesel and gasoline engines operating in severe driving conditions typically encountered in city operations. This product is recommended by ExxonMobil for European, Russian and American engines for use in a wide range of traditional light-duty commercial vehicles.

Mobil Delvac Light Commercial Vehicle 10W-40 is engineered with a blend of advanced technology base stocks and additive system to provide a strong foundation for oxidation resistance, soot handling, and wear control supplemented with excellent piston deposit protection and reduced sludge formation to help provide long engine life.

### Features and Benefits

Mobil Delvac Light Commercial Vehicle 10W-40 is formulated from high performance base oils and a superior balanced additive system to provide optimum engine performance in modern diesel and gasoline engines as well as older models. Key benefits include:

Features	Advantages and Potential Benefits
Increased thermal and oxidation stability	Help to reduced sludge build-up, deposits, and long oil and engine life
Enhanced wear protection	Helps towards long component and engine life
Improved corrosion protection	Helps to reduce bearing wear to assist with long drain intervals in modern diesel engines
Advanced piston deposit control	Helps to keep engines clean with reduced maintenance costs and long engine life
Advanced soot handling to control viscosity increase, sludge build up, and filter pressure	Helps to enhance engine protection for long engine life
Enhanced low temperature pumpability	Fast start up with reduced wear operating in low temperature climates

### Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered engines built by European, Russian, and American manufacturers
- On-highway light trucking including mixed fleets with gasoline engines.
- For GAZ Light Duty Vehicles with diesel or petrol engines requiring API CI-4 or API SL motor oils

### Specifications and Approvals

<b>This product has the following approvals:</b>
Cummins CES 20078

**This product has the following approvals:**

Cummins CES 20077

DTFR 15B110

**This product has the following builder approvals:**

AVTODISEL (YaMZ) YaMZ-6-12

**This product is recommended by ExxonMobil for use in applications requiring:**

ACEA B2-98 Issue 2

ACEA A2-96 Issue 3

API CG-4

API CF-4

API CF

CUMMINS CES 20072

CUMMINS CES 20071

**This product meets or exceeds the requirements of the following industry specification:**

API CI-4

API CH-4

API SL

API SJ

CUMMINS CES 20076

**This product meets or exceeds the requirements of:**

ACEA E7

**Properties and Specifications**

Property	
Grade	SAE 10W-40
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.8
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	100

Property	
Viscosity Index, ASTM D2270	154
Ash, Sulfated, mass%, ASTM D874	1.2
Total Base Number, mgKOH/g, ASTM D2896	11.1
Pour Point, °C, ASTM D97	-36
Flash Point, Cleveland Open Cup, °C, ASTM D92	210
Density @ 15 C, g/ml, ASTM D1298	0.868

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2024

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved