

## Mobil Super™ 2000 X1 5W-30

Mobil Passenger Vehicle Lube, Belarus

Premium Semi-Synthetic Passenger Vehicle Motor Oil

### **Product Description**

Mobil Super™ 2000 x1 5W-30 is a synthetic technology engine oil that provides everyday protection against sludge and wear to ensure long engine life.

### Features and Benefits

Mobil Super 2000 products are industry proven so you can trust you will get the protection you want from your vehicle. Mobil Super 2000 x1 5W-30, confidence in every journey, provides multiple benefits:

- •Reliable wear protection
- •High level of sludge prevention
- Engine long life and cleanliness
- •Cold start-up protection
- •Reliable high temperature protection

### Applications

ExxonMobil recommends Mobil Super 2000 x1 5W-30 for:

- •Older engine technologies
- •Gasoline and Diesel without Diesel Particulate Filters (DPF)
- •Passenger cars, SUV's, light trucks and vans
- •Highway cruising and stop-and-go city driving
- •Normal to occasionally severe operating conditions
- •Standard oil drain up to 15.000km/1 year

### Specifications and Approvals

# This product has the following approvals:

VW 502 00

#### This product is recommended for use in applications requiring:

API CF

ACEA A3/B3-16

# This product meets or exceeds the requirements of:

API SL

ACEA A3/B4

### Properties and Specifications

Property	
Grade	SAE 5W-30
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	73.9
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	12.2
Ash, Sulfated, mass%, ASTM D874	1.2
Phosphorus, mass%, ASTM D4951	0.10
Flash Point, Cleveland Open Cup, °C, ASTM D92	235
Density @ 15.6 C, g/ml, ASTM D4052	0.86
Pour Point, °C, ASTM D97	-33

## Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise. 08-2024

