



Mobil 1™ FS X1 5W-50

Mobil Passenger Vehicle Lube , Belarus

Advanced Full Synthetic Motor Oil

Product Description

Mobil 1™ is the world's leading synthetic motor oil brand delivering our ultimate performance and protection. The Mobil 1 technology keeps your engine running like new. Mobil 1™ FS x1 5W-50 is an advanced performance synthetic engine oil designed to help provide exceptional cleaning power.

Features and Benefits

Mobil 1™ FS x1 5W-50 is made with a proprietary blend of high performance synthetic base stocks fortified with a precisely balanced component system providing:

- Engine wear protection and lubrication over the full oil drain interval.
- Excellent protection for your engine by helping to prevent the buildup of harmful deposits
- Enhanced cleaning technology for cars with higher mileage; 100 000km +
- Improved protection against variable fuel quality*
- Protection for your engine during start-up at low temperatures

* Performance compared in industry standard tests, which use fuels designed to promote sludge formation.

Applications

Mobil 1 FS x1 5W-50 is recommended for many types of vehicles with higher mileage; > 100 000 km

Specifications and Approvals

| |
|--|
| This product has the following approvals: |
| MB-Approval 229.1 |
| MB-Approval 229.3 |
| Porsche A40 |

| |
|---|
| This product is recommended for use in applications requiring: |
| API CF |
| FIAT 9.55535-M2 |

| |
|---|
| This product meets or exceeds the requirements of: |
| API SM |

This product meets or exceeds the requirements of:

API SN

ACEA A3/B3

ACEA A3/B4

LEXUS LFA Service Fill

Properties and Specifications

| Property | |
|---|-----------|
| Grade | SAE 5W-50 |
| Noack Volatility, 1 h, 250 C, mass%, ASTM D5800 | 75 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 16.7 |
| Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684 | 23000 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 240 |
| Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683 | 4.5 |
| Base Number, mgKOH/g, ASTM D2896 | 13 |
| Cold-Cranking Simulator, Apparent Viscosity @ -30 C, mPa.s, ASTM D5293 | 6000 |
| Shear Stability, Kinematic Viscosity @ 100 C, after Shear, mm ² /s, ASTM D6278 | 16.6 |
| Pour Point, °C, ASTM D97 | -45 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2020

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved