



## Mobil Super™ 2000 x3 5W-40

Mobil Passenger Vehicle Lube , Belarus

Premium Semi-Synthetic Passenger Vehicle Engine Oil - Everyday Protection

### Product Description

Mobil Super™ 2000 x3 5W-40 is a synthetic technology engine oil that provides everyday protection against wear and sludge to ensure long engine life.

### Product Benefits

Mobil Super 2000 products are industry proven, so you can trust your engine will get the protection it needs. Mobil Super 2000 x3 5W-40, confidence in every journey, provides multiple benefits:

- Reliable wear protection
- High level of sludge prevention
- Engine long life and cleanliness
- Cold start-up protection
- Reliable high temperature protection

### Applications

ExxonMobil recommends Mobil Super 2000 x3 5W-40 for:

- Older engine technologies
- Gasoline and Diesel without Diesel Particulate Filters (DPF)
- Passenger cars, SUV's, light trucks and vans
- Highway cruising and stop-and-go city driving
- Normal to occasionally severe operating conditions

### Specifications and Approvals

| This product has the following approvals: |
|---|
| AVTOVAZ (LADA cars)                       |
| MB-Approval 229.3                         |
| VW 502 00                                 |
| VW 505 00                                 |

| This product meets or exceeds the requirements of: |
|--|
| ACEA A3/B4   |
| API SN PLUS  |
| AAE (STO 003) Group B7                             |

**This product meets or exceeds the requirements of:**

ACEA A3/B3

### Properties and Specifications

| Property   |           |
|--|-----------|
| Grade  | SAE 5W-40 |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445  | 80.8      |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445 | 13.2      |
| Viscosity Index, ASTM D2270                                | 165       |
| Pour Point, °C, ASTM D97                                   | -39       |
| Phosphorus, mass%, ASTM D4951                              | 0.10      |
| Ash, Sulfated, mass%, ASTM D874                            | 1.0       |
| Flash Point, Cleveland Open Cup, °C, ASTM D92              | 225       |
| Density @ 15 C, g/ml, ASTM D1298                           | 0.859     |

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2020

Energy lives here™

**ExxonMobil**



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved