



## MOBIL DELVAC HD MIXED FLEET ELC ANTIFREEZE COOLANT 50 50 PREDILUTED

Mobil Commercial Vehicle Lube , Canada

### Product Description

MOBIL DELVAC HD MIXED FLEET ELC ANTIFREEZE / COOLANT 50/50 PREDILUTED is designed for complete mixed fleet use. Product is recommended for use in many makes and models of foreign and domestic passenger vehicles, light duty and heavy duty diesel applications.

### Features and Benefits

- Rated up to 6 years, 12,000 hours, or 960,000 km,
- Low silicate formula,
- Borate, Nitrite, Amine and Phosphate free,
- Protects against rust, corrosion and pitting for all coolant system metals including aluminum,
- Provides exceptional boil-over and freeze protection when used in accordance with OEM and product manufacturer's guidelines regarding product dilution

### Typical Properties

| Specific Gravity 15.6 °C  | 1.12 Min. | 1.14 Max.   |
|---------------------------|-----------|-------------|
| Freeze Point, 50 Vol%, °C |           | -37 Max.    |
| PH, 50 volume %           | 7.6 Min.  | 9.0 Max.    |
| Foam, Volume              |           | 150 Max.    |
| Chloride, PPM             |           | 25 Max.     |
| Color                     |           | Pale Yellow |
| Density @ 15.5 °C (g/ml)  | 1.122     |             |

### Health And Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

Mobil logotype, the Pegasus design, and Mobil Delvac are trademarks of Exxon Mobil Corporation, or one of its subsidiaries. Imperial Oil, licensee

07-2020

#### Imperial Oil

Petroleum and Chemicals Division

Lubricants and Specialties

240 Fourth Ave SW

C. P. 2480, Station M

Calgary AB T2P 3 M 9

1-800-268-3183

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local Imperial Oil contact or visit [www.imperialoil.ca](http://www.imperialoil.ca) ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Imperial Oil, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved