



MOBIL DELVAC HD OAT M&N HEAVY DUTY DIESEL ELC ANTIFREEZE COOLANT 50 50 PREDILUTED

Mobil Commercial Vehicle Lube , Canada

Product Description

MOBIL DELVAC HD OAT M&N HEAVY DUTY DIESEL ELC ANTIFREEZE / COOLANT 50/50 PREDILUTED is designed for heavy duty diesel applications where extended service interval and aluminum compatibility is required. Product is recommended for use in all on-road and off-road vehicles including, but not limited to, Caterpillar, Cummins, Detroit, MTU, GM Heavy Truck, Freightliner, PACCAR/DAF, and Volvo/Mack.

Features and Benefits

- Rated up to 8 years, 15,000 hours, or 1,200,000 km
- CAT EC-1 compatible
- Excellent high temperature corrosion performance
- OAT based
- 2-EHA free (2 ethylhexanoic acid)
- Excellent heat transfer capability
- Excellent liner cavitation performance
- Borate, Phosphate and Silicate free

Applications

MOBIL DELVAC HD OAT M&N HEAVY DUTY DIESEL ELC ANTIFREEZE / COOLANT 50/50 PREDILUTED is designed for heavy duty diesel applications where extended service interval and aluminum compatibility is required

Typical Properties

Specific Gravity 15.6 °C	1.125 Min.	1.135 Max.
Freeze Point, 50 Vol%, °C		-37 Max.
PH, 50 volume %	7.8 Min.	8.5 Max.
Foam, Volume		150 Max.
Chloride, PPM		25 Max.
Color		Red
Density @ 15.5 °C (g/ml)	1.1254	

Health And Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2020

Imperial Oil

Petroleum and Chemicals Division

Lubricants and Specialties

240 Fourth Ave SW

C. P. 2480, Station M

Calgary AB T2P 3 M 9

1-800-268-3183

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved