



Mobil Delvac™ 1330, 1340

Mobil Commercial Vehicle Lube , Canada

High Performance Diesel Engine Oils

Product Description

Mobil Delvac™ 1330 and 1340 are high performance monograde diesel engine oils formulated from advanced technology base oils and a balanced additive system. They are specifically engineered for performance 2-stroke diesel engines operating under severe conditions in both on-road and off-road applications. Mobil Delvac 1300 monogrades are used in a wide range of applications where a monograde lubricant is recommended.

Features and Potential Benefits

Features	Advantages and Potential Benefits
Excellent protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion	Prolonged engine life Less wear Excellent protection against ring sticking
Extended TBN reserve	Long-term deposit/wear control Controls formation of acids when using higher sulfur fuels

Applications

- On-road light and heavy -duty trucking
- Off-road industries including: construction, mining, quarrying, and agriculture

Specifications and Approvals

Mobil Delvac 1300 Monogrades are recommended for use in applications requiring:	Mobil Delvac 1330	Mobil Delvac 1340
API CF, CD	X	X
API CF-2, CD-II	X	X
API SL, SJ, SH	X	X
Mack EO-K/2	X	X
Allison C-4	X	
Caterpillar TO-2	X	X
Vickers 35VQ25	X	X

Typical Properties

Mobil Delvac 1300 Monogrades	Mobil Delvac 1330	Mobil Delvac 1340
SAE Grade	30	40
Viscosity, ASTM D445		

Mobil Delvac 1300 Mongrades	Mobil Delvac 1330	Mobil Delvac 1340
cSt @ 40°C	102	137
cSt @ 100°C	12.0	14.3
Viscosity Index, ASTM D2270	108	102
Sulfated Ash, wt%, ASTM D874	1.0	1.0
Total Base Number, ASTM D2896	8.2	8.2
Pour Point, °C, ASTM D5949	-24	-15
Flash Point, °C, ASTM D92	238	242
Colour, ASTM D1500	3.0	3.0
Density, kg/m ³ @ 15°C, ASTM D4052	888	890

Health and Safety

The products described on this data sheet are manufactured from high quality petroleum base stocks, carefully blended with selected additives. As with all petroleum products, good personal hygiene and careful handling should always be practiced. Avoid prolonged contact to skin, splashing into the eyes, ingestion or vapour inhalation. Please refer to the Material Safety Data Sheet for further information.

Note: The products described on this data sheet are NOT controlled under Canadian WHMIS legislation.

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2019

Imperial Oil

Petroleum and Chemicals Division
Lubricants and Specialties
240 Fourth Ave SW
C. P. 2480, Station M
Calgary AB T2P 3 M 9
1-800-268-3183

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved