



Mobilube™ HD Extra

Mobil Commercial Vehicle Lube , Canada

High Performance Commercial Gear Lubricants

Product Description

Mobilube™ HD Extra MG 75W is a high performance commercial gear lubricant formulated from select base oils and an advanced additive system. This lubricant is engineered for performance in heavy-duty commercial manual transmissions, axles, and final drives where severe service with shock loading is expected. It provides an excellent chemical and thermal stability at elevated bulk oil temperatures, good performance at low temperatures, and good rust protection resulting from water contamination and wet conditions. It will provide excellent performance in applications where API GL-6 (Mobilube HD Extra 80W-140) or GL-6/GL-5 (Mobilube Extra MG 75W) lubricants are required. API GL-6 denotes lubricants intended for gears with very high pinion offset where protection from gear scoring in excess of that provided by GL-5 lubricants is required. API GL-6 is no longer active as the original test equipment and procedures are obsolete.

Features and Benefits

Today's heavy equipment applications place higher performance demands on drive train lubricants. Higher speeds, higher torque, and heavier loads require improved formulations to maximize equipment life and optimize operating costs. Longer service intervals place additional demands on the gear lubricant. Mobilube HD Extra gear lubricants are engineered to meet these challenges. The key benefits include:

Features	Advantages and Potential Benefits
Excellent thermal stability and resistance to high temperature oxidation	Extended gear and bearing life due to minimal deposits and longer seal life
Good protection against low speed/high torque wear and against high speed scoring	Increased load carrying capability and reduced operating costs
Excellent rust, staining, and corrosion protection	Reduced wear and longer component life
Effective low temperature lubrication	Reduced wear and ease of start-up
Wide multipurpose capability	Reduced number of gear lubricants to simplify inventory and minimize misapplication
Good resistance to foaming	Maintains film strength for effective lubrication
Compatible with typical automotive seals and gaskets	Minimum leakage and reduced contamination

Applications

- Heavy-duty manual transmissions, axles, and final drives requiring API GL-6 (inactive) or GL-5 level performance
- On-highway light and heavy-duty trucks, busses, vans, and cars
- Off-highway industries including: construction, mining, quarrying, and agriculture
- Other heavy-duty industrial and automotive applications involving hypoid and other gears operating under conditions where high speed/shock load, high speed/low torque, and/or low speed/high torque conditions prevail
 - Mobilube HD Extra gear lubricants are intended for top-off, and refill of enclosed commercial gearing in manual or semiautomatic transmissions where gear lubricants are recommended including drive axles and final drives
- Not recommended for applications requiring API GL-4 Level performance
- Not intended for transmissions for which engine oil or automatic transmission fluids are recommended

Specifications and Approvals

This product is recommended for use in applications requiring:	MG 75W
API GL-5	X
API GL-6	X

Properties and Specifications

Property	MG 75W
Grade	SAE 75W
Density @ 15 C, g/ml, ASTM D4052	0.903
Flash Point, Cleveland Open Cup, °C, ASTM D92	150
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	15.9
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	93
Pour Point, °C, ASTM D97	-48
Viscosity Index, ASTM D2270	182

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2021

Imperial Oil

Petroleum and Chemicals Division

Lubricants and Specialties

240 Fourth Ave SW

C. P. 2480, Station M


Calgary AB T2P 3 M 9

1-800-268-3183

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2023 Exxon Mobil Corporation. All

Rights Reserved