



## Mobiltac 50M Series

Mobil Industrial , Canada

OPEN GEAR LUBRICANT

### Product Description

The Mobiltac 50M Series of premium performance open gear lubricants is designed to provide outstanding protection of heavily loaded open gears exposed to operating conditions. Mobiltac 50M is a semi-synthetic open gear lubricant containing high performance additives designed to provide an adhesive film and ex load carrying capability particularly for open gears on shovels, draglines, and associated mining equipment.

### Features and Benefits

Mobiltac 50M has the following features and potential benefits:

- Very high viscosity, semi synthetic lubricant designed to extend component life in heavily loaded open gear applications
- Excellent wash-off resistance in very wet operating environments
- Solid anti-wear and extreme pressure protection of mating surfaces against damaging wear in contact zones
- Available in three grades for different ambient operating conditions.
- Mobiltac 50M Heavy is recommended for ambient temperatures >20°F (-7°C) Mobiltac 50M Light is recommended for ambient temperatures from -15°F (-25°C) to 70°F (21°C) while Mobiltac 50M Arctic is recommended for ambient temperatures <50°F (10°C).
- Weld load protection > 800 kg

### Applications

Mobiltac 50M is recommended for the lubrication of:

- Open gears on shovels, draglines and associated mining equipment with spray, brush or drip application
- The hoist gear on Caterpillar Mining electric rope shovels and in applications where an extra heavy open gear lubricant is desired

### Properties and Specifications

Property	MOBILTAC 50M HEAVY	MOBILTAC 50M LIGHT	MOBILTAC 50M ARC
Appearance, Visual	Viscous Semi-Fluid	Viscous Semi-Fluid	Viscous Semi-Fluid
Color, Visual	Black	Black	Black
Copper Strip Corrosion, Rating, ASTM D4048	1A	1A	
Flash Point, °C, ASTM D92	300°F (149°C)	284°F (140°C)	290°F (143°C)
Four-Ball Extreme Pressure Test, without Diluent, Weld Point, kgf, ASTM D2596	>800	>800	>800
Rust, Rating, ASTM D1743	PASS	Pass	Pass
Ventmeter, 600, psi, Lincoln VE-1	20°F @ <30 sec	-15°F @ <150 sec	-30°F @ <150 sec
Viscosity @ 40 C, Base Oil, mm <sup>2</sup> /s, ASTM D445	50,000 cSt	50,000 cSt	50,000 cSt

### Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2023

Imperial Oil

Petroleum and Chemicals Division  
Lubricants and Specialties  
240 Fourth Ave SW  
C. P. 2480, Station M  
Calgary AB T2P 3 M 9  
  
1-800-268-3183

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)  
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

ExxonMobil

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved